




Dławnica izolacyjna DP

z gwintem PG

Materiał poliamid 6
Temperatura pracy -30 ÷ +80 °C
Kolor szary RAL 7035 (inne kolory po uzgodnieniu)
Stopień ochrony IP54

IP54

Uwaga! Dławnica w komplecie z nakrętką.



Typ	Art. nr	Średnica zewnętrzna przewodu [mm]	Gwint PG	Wymiary [mm]		Wymiar pod klucz [mm]		szt
				E	H	A	B	
DP 7	E03DK-01010100101	3,0÷6,0	P7	6,5	17	13	15	100
DP 9	E03DK-01010100201	5,0÷7,0	P9	7,0	18	17	19	100
DP 11	E03DK-01010100301	6,0÷9,0	P11	8,0	18	19	22	100
DP 13	E03DK-01010100401	9,0÷12,0	P13,5	9,0	20	22	24	100
DP 16	E03DK-01010100501	11,0÷14,0	P16	9,0	20	24	27	100
DP 21	E03DK-01010100601	14,0÷18,0	P21	10,0	28	30	32	50
DP 29	E03DK-01010100701	18,0÷25,0	P29	12,0	28	41	41	50
DP 36	E03DK-01010100801	25,0÷32,0	P36	14,0	34	50	55	10

