

Seria EUREKA - MIL

Normy: EN 60309-1, EN 60309-2

WTYCZKI - IP67

do zastosowań wojskowych

Kolor: zielony



Proste							
	Opis	Kolor	Opakowanie	Nr katalogowy			
16A	2P+ E 6h 50/60 Hz 200-250V	■	10/50	216.81633			
	3P+ E 6h 50/60 Hz 380-415V	■	10/50	216.81636			
	3P+N+E 6h 50/60 Hz 346-415V	■	10/50	216.81637			
32A	2P+ E 6h 50/60 Hz 200-250V	■	10/40	216.83233			
	3P+ E 6h 50/60 Hz 380-415V	■	10/40	216.83236			
	3P+N+E 6h 50/60 Hz 346-415V	■	10/40	216.83237			
63A	2P+E 6h 50/60 Hz 200-250V	■	1/1	215.86333			
	3P+E 6h 50/60 Hz 380-415V	■	1/1	215.86336			
	3P+N+E 6h 50/60 Hz 346-415V	■	1/1	215.86337			
125A	2P+E 6h 50/60 Hz 200-250V	■	1/1	215.812533			
	3P+E 6h 50/60 Hz 380-415V	■	1/1	215.812536			
	3P+N+E 6h 50/60 Hz 346-415V	■	1/1	215.812537			

GNIAZDA PRZENOŚNE - IP67

do zastosowań wojskowych

Kolor: zielony



Proste							
	Opis	Kolor	Opakowanie	Nr katalogowy			
16A	2P+ E 6h 50/60 Hz 200-250V	■	10/40	316.81643			
	3P+ E 6h 50/60 Hz 380-415V	■	10/40	316.81646			
	3P+N+E 6h 50/60 Hz 346-415V	■	10/40	316.81647			
32A	2P+ E 6h 50/60 Hz 200-250V	■	10/40	316.83243			
	3P+ E 6h 50/60 Hz 380-415V	■	10/40	316.83246			
	3P+N+E 6h 50/60 Hz 346-415V	■	10/40	316.83247			
63A	2P+E 6h 50/60 Hz 200-250V	■	1/1	315.86343			
	3P+E 6h 50/60 Hz 380-415V	■	1/1	315.86346			
	3P+N+E 6h 50/60 Hz 346-415V	■	1/1	315.86347			
125A	2P+E 6h 50/60 Hz 200-250V	■	1/1	315.812543			
	3P+E 6h 50/60 Hz 380-415V	■	1/1	315.812546			
	3P+N+E 6h 50/60 Hz 346-415V	■	1/1	315.812547			

GNIAZDA TABLICOWE - IP67

do zastosowań wojskowych

Kolor: zielony



Proste							
	Opis	Kolor	Opakowanie	Nr katalogowy			
16A	2P+ E 6h 50/60 Hz 200-250V	■	10/100	247.81693			
	3P+ E 6h 50/60 Hz 380-415V	■	10/100	247.81696			
	3P+N+E 6h 50/60 Hz 346-415V	■	10/100	247.81697			
32A	2P+ E 6h 50/60 Hz 200-250V	■	10/50	247.83293			
	3P+ E 6h 50/60 Hz 380-415V	■	10/50	247.83296			
	3P+N+E 6h 50/60 Hz 346-415V	■	10/50	247.83297			
63A	2P+E 6h 50/60 Hz 200-250V	■	1/10	247.86393			
	3P+E 6h 50/60 Hz 380-415V	■	1/10	247.86396			
	3P+N+E 6h 50/60 Hz 346-415V	■	1/10	247.86397			
125A	2P+E 6h 50/60 Hz 200-250V	■	1/1	247.812593			
	3P+E 6h 50/60 Hz 380-415V	■	1/1	247.812596			
	3P+N+E 6h 50/60 Hz 346-415V	■	1/1	247.812577			

Seria OPTIMA

Normy: EN 60309-1, EN 60309-2

WTYCZKI ODBIERNIKOWE - IP44

Wymiary: 70x87 mm



90°							
	Opis	Kolor	Opakowanie	Nr katalogowy			
16A	2P+ E 6h 50/60 Hz 200-250V	■	10/100	242.1693			
	3P+ E 6h 50/60 Hz 380-415V	■	10/100	242.1696			
	3P+N+E 6h 50/60 Hz 346-415V	■	10/60	242.1697			
32A	2P+ E 6h 50/60 Hz 200-250V	■	10/60	242.3293			
	3P+ E 6h 50/60 Hz 380-415V	■	10/60	242.3296			
	3P+N+E 6h 50/60 Hz 346-415V	■	10/60	242.3297			

		A	B	C	D	E	F	G	H	I
16A	2P+ ±	70	87	56	70	5,2	73	65	83	142
	3P+ ±	70	87	56	70	5,2	73	65	91	143
	3P+N+ ±	70	87	56	70	5,2	73	65	97	144
32A	2P+ ±	70	87	56	70	5,2	87	76	99	153
	3P+ ±	70	87	56	70	5,2	87	76	99	153
	3P+N+ ±	70	87	56	70	5,2	87	76	107	154

WTYCZKI ODBIERNIKOWE - IP67

Wymiary: 70x87 mm



90°							
	Opis	Kolor	Opakowanie	Nr katalogowy			
16A	2P+ E 6h 50/60 Hz 200-250V	■	10/100	247.1693			
	3P+ E 6h 50/60 Hz 380-415V	■	10/60	247.1696			
	3P+N+E 6h 50/60 Hz 346-415V	■	10/50	247.1697			
32A	2P+ E 6h 50/60 Hz 200-250V	■	10/40	247.3293			
	3P+ E 6h 50/60 Hz 380-415V	■	10/40	247.3296			
	3P+N+E 6h 50/60 Hz 346-415V	■	10/40	247.3297			

		A	B	C	D	E	F	G	H	I	L
16A	2P+ ±	70	87	56	70	5,2	73	65	93	142	73
	3P+ ±	70	87	56	70	5,2	73	65	102	143	81
	3P+N+ ±	70	87	56	70	5,2	73	65	109	144	88
32A	2P+ ±	70	87	56	70	5,2	87	76	111	153	93
	3P+ ±	70	87	56	70	5,2	87	76	111	153	93
	3P+N+ ±	70	87	56	70	5,2	87	76	120	154	101