

Seria OPTIMA

Normy: EN 60309-1, EN 60309-2

GNIAZDA STAŁE - IP44



Skośne							
Opis				Kolor	Opakowanie	Nr katalogowy	
16A	2P+ E	6h	50/60 Hz	200-250V		10/40	513.1653
	3P+ E	6h	50/60 Hz	380-415V		10/40	513.1656
	3P+N+E	6h	50/60 Hz	346-415V		10/40	513.1657
32A	2P+ E	6h	50/60 Hz	200-250V		1/10	513.3253
	3P+ E	6h	50/60 Hz	380-415V		1/10	513.3256
	3P+N+E	6h	50/60 Hz	346-415V		1/10	513.3257



(TOP) Puszka - 3-otworowa (wersja podstawowa)							
Opis				Kolor	Opakowanie	Nr katalogowy	
16A	2P+ E	6h	50/60 Hz	200-250V		10/40	513.1653T
	3P+ E	6h	50/60 Hz	380-415V		10/40	513.1656T
	3P+N+E	6h	50/60 Hz	346-415V		10/40	513.1657T
32A	2P+ E	6h	50/60 Hz	200-250V		1/10	513.3253T
	3P+ E	6h	50/60 Hz	380-415V		1/10	513.3256T
	3P+N+E	6h	50/60 Hz	346-415V		1/10	513.3257T

Seria OPTIMA

Normy: EN 60309-1, EN 60309-2

GNIAZDA STAŁE - IP67



(TOP) Puszka - 3-otworowa (szybko-złącza zaciskane wersja podstawowa)							
Opis				Kolor	Opakowanie	Nr katalogowy	
16A	2P+ E	6h	50/60 Hz	200-250V		10/50	518.1653T
	3P+ E	6h	50/60 Hz	380-415V		10/50	518.1656T
	3P+N+E	6h	50/60 Hz	346-415V		10/40	518.1657T
32A	2P+ E	6h	50/60 Hz	200-250V		10/40	518.3253T
	3P+ E	6h	50/60 Hz	380-415V		10/40	518.3256T
	3P+N+E	6h	50/60 Hz	346-415V		10/40	518.3257T



(TOP) Puszka - 3-otworowa (szybko-złącza zaciskane - wersja podstawowa)							
Opis				Kolor	Opakowanie	Nr katalogowy	
16A	2P+ E	6h	50/60 Hz	200-250V		10/50	518.1653TF
	3P+ E	6h	50/60 Hz	380-415V		10/50	518.1656TF
	3P+N+E	6h	50/60 Hz	346-415V		10/40	518.1657TF
32A	2P+ E	6h	50/60 Hz	200-250V		10/40	518.3253TF
	3P+ E	6h	50/60 Hz	380-415V		10/40	518.3256TF
	3P+N+E	6h	50/60 Hz	346-415V		10/40	518.3257TF