cmco C

15

Design

Size mm PU Article no.



made of non-conducting, non-warping plastic, with 1 horizontal and 1 vertical bubble level

400 mm	24 x 52 mm	1	21 1435	
800 mm	24 x 52 mm	1	21 1437	

with three levels (1 x horizontal, 1 x vertical,  $1 \times 45^{\circ}$ ), made of non-conductive, distortion-free plastic with ergonomic recessed grips and a patented level housing

600 mm	32 x 58 mm	1	21 1536	

## Switch cabinet spirit level

torpedo-shaped, with three levels which are easy to read (1 x horizontal, 1 x vertical, 1 x 45°), a magnetic V-ledge for pipes or cables as well as robust rubber end caps

230 mm	18 x 38 mm 1	21 1540	
--------	--------------	---------	--

# Switch cabinet spirit level

with Plumb Site® Dual-View™ level, made of non-conductive plastic with a robust aluminium rail and integrated magnetic ledge, three levels (1  $\times$  horizontal, 1  $\times$  vertical, 1  $\times$  45°)

250 mm	16 x 55 mm	1	21 1542	

## Measurement and marking spirit level

made of aluminium, in a stable, triangular design, two inserted levels (horizontal, vertical), two slide markers, mm and cm scale, as well as zero point and central point indicators, slider with blade guide for cutting paper, removable nail gripper to remove nails from walls. The 2 adjustable sliders have been set into the aluminium profile to enable more precise display of drill holes in horizontal or vertical arrangement. Ideal as a marking template for setting switch boxes.

600 mm	28 x 40 mm	1	21 1550	

### Electrician's spirit level

with four fixed marker point at 71 mm intervals which keep to a precise switch or socket distance, with two levels (horizontal, vertical), with a milled surface and shock-absorbing end caps.

20 x 50 mm 1	21 1552	
	20 x 50 mm 1	20 x 50 mm 1 21 1552

### Mini spirit level

Box section made of aluminium, with shock-resistant plastic level, certified accuracy, shock-resistant end caps. Practical for any tool belt and small pockets.

### Lightweight metal spirit level

with Plumb Site® Dual-View™ level. Two levels (horizontal, vertical) with a milled surface and shock-absorbing end caps.

400 mm	20 x 50 mm	1	21 1520	
600 mm	20 x 50 mm	1	21 1522	
800 mm	20 x 50 mm	1	21 1523	
1000 mm	20 x 50 mm	1	21 1524	
with two magnets				
600 mm	20 x 50 mm	1	21 1526	

