A COMPANY

Design

Digital Multimeter

Highlights

- CAT III 600 V
- 2000 counts
- Manual range
- Non-contact voltage testing
- DC current measurement range
- Temperature measurement
- Torch function and display lighting
- 600 V high capacity fuses

Scope of delivery

- Test leads
- K-type thermo sensor
- 9 V battery
- User manual

Features

- Diode test
- Acoustic continuity test
- Non-contact AC voltage tester
- Hold function
- Low-Batt display
- Sturdy housing with soft rubber protection

Size mm PU Article no.

Digital Multimeter

Highlights

- CAT III 600 V
- 2000 counts
- · Measurement jack display
- Manual range
- For professional use, in household and hobby

Scope of delivery

- Test leads
- 9 V battery
- User manual

Features

- Standard measurement ranges V/DC, V/AC, A/DC, A/AC
- Resistance
- Diode test
- · Acoustic continuity test
- Battery test for 1.5 and 9 V batteries
- · Impedance switching
- · Low-Batt display
- Digit height 19 mm
- Sturdy housing with soft rubber protection

11 1408

Clip-on adapter

can be used in combination with any digital multimeter with a range of 200 mV/2 V alternating current to carry out current measurements. The connection is made directly at the 4 mm input jack on the multimeter.

- Measurement range: 0 A to 300 A at 1.5% \pm 2 A $\,$ Conversion 1 A AC corresponds to 1 mV
- Operating temperature: 0 °C to 50 °C
- Width of opening max. 28 mm

11 1414

AC mini ammeter

Highlights

- CAT III 600 V
- AC current measurement (AVG) up to 400 A
- Non-contact voltage tester

Scope of delivery

- 2 micro batteries (type AAA)
- Bag
- · Safety test leads
- · Thermal probe
- K-type measurement adapter
- User manual

Features

- Data-Hold
- Auto-Power-Off function
- · Voltage, frequency, temperature, capacity and resistance measurement function
- Diode test and acoustic continuity test
- Non-contact voltage tester (NCV)