

Amp.	Styki	pakowane po/szt.	Nr kat.	Amp.	Styki	pakowane po/szt.	Nr kat.
16	3		ts613g	63	3		
16	4		ts614g	63	4		ts635g
16	5		ts615g	63	5		
32	3		ts623g	125	3		
32	4		ts625g	125	4		ts645g
32	5			125	5		



16	3	10	20163
16	4	10	20164
16	5	10	20165
32	3	10	203234
32	4	10	
32	5	10	20325



0152-6TT + 20165



63	3		ts7632g
63	4		
63	5		
125	3		ts1252g
125	4		
125	5		



Dławnice kablowe IP68, czarne

Uwaga: Dla wejść bez gwintów, powinny zostać użyte odpowiednie nakrętki.

Rozmiar	Dł.gwintu	Średnica przewodu	Nr kat.	Pakowane po
M20 x 1,5	15 mm	6-12 mm	M20_CZ	50
M25 x 1,5	15 mm	13-18 mm	M25_CZ	50
M32 x 1,5	15 mm	18-25 mm	M32_CZ	25
M40 x 1,5	18 mm	22-32 mm	M40_CZ	10
M50 x 1,5	18 mm	32-38 mm	M50_CZ	5
M63 x 1,5	18 mm	37-44 mm	M63_CZ	5
M40 x 1,5	Nakrętka, Mosiądz pokryty niklem		M40_MOS NAKR.	50
M50 x 1,5	Nakrętka, Mosiądz pokryty niklem		M50_MOS NAKR.	50

