



## Podstawa bezpiecznikowa do wkładek cylindrycznych

Typ **Z-SHL/1N**  
 Catalog No. **263884**

## Dane techniczne zgodne z ETIM 6.0

|                                                                                                                                                                                                                 |    |                  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|------------------|
| Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)                                                                                                                              |    |                  |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ecI@ss8.1-27-37-14-01 [AKF058010]) |    |                  |
| Version as main switch                                                                                                                                                                                          |    | No               |
| Version as safety switch                                                                                                                                                                                        |    | No               |
| Max. rated operation voltage Ue AC                                                                                                                                                                              | V  | 230              |
| Rated permanent current Iu                                                                                                                                                                                      | A  | 32               |
| Rated operation power at AC-23, 400 V                                                                                                                                                                           | kW | 0                |
| Conditioned rated short-circuit current Iq                                                                                                                                                                      | kA | 10               |
| Rated short-time withstand current Icw                                                                                                                                                                          | kA | 0                |
| Suitable for fuses                                                                                                                                                                                              |    | Shape C1-C3      |
| Number of poles                                                                                                                                                                                                 |    | 2                |
| With error protection                                                                                                                                                                                           |    | No               |
| Type of electrical connection of main circuit                                                                                                                                                                   |    | Screw connection |
| Suitable for ground mounting                                                                                                                                                                                    |    | No               |
| Suitable for front mounting 4-hole                                                                                                                                                                              |    | No               |
| Suitable for busbar mounting                                                                                                                                                                                    |    | No               |
| Type of control element                                                                                                                                                                                         |    | Other            |
| Position control element                                                                                                                                                                                        |    | Front side       |
| Motor drive optional                                                                                                                                                                                            |    | No               |
| Motor drive integrated                                                                                                                                                                                          |    | No               |
| Version as emergency stop installation                                                                                                                                                                          |    | No               |
| Degree of protection (IP), front side                                                                                                                                                                           |    | IP20             |