

Design	Size mm	PU	CIMCO-item no.
--------	---------	----	----------------



Product video  
click 'n' crimp

★ TOPSELLER ★



These symbols help you to select the right tool for the corresponding connecting material.

<b>IS</b> insulated connectors (red/blue/yellow)	<b>Q</b> Crimp cable lugs	<b>AL</b> Aluminum-copper compression connector
<b>FL</b> non-insulated flat connectors	<b>R</b> Tubular cable lugs	<b>VA</b> Stainless steel (VA) tube cable lugs
<b>AE</b> ferrules	<b>F</b> Tubular cable lugs fine stranded conductors	<b>RU</b> Round press inserts for round of sector-shaped conductors
<b>ZAE</b> twin wire end ferrules	<b>D</b> crimp cable lugs according to DIN	

CLICK 'N' CRIMP

Crimping pliers with interchangeable crimping profile inserts, fixed by a catch holder in the tool body. Two further crimping profiles are held captive in the legs of the pliers. Tool body is made of strong, specially tempered, hardened sheet steel, with leverage transfer for reduced use of manual force, adjustable ratchet mechanism with automatic release for standard-compliant crimping pressure, ergonomic 2-component handle sleeves, Weight including 3 crimping profile inserts, only 690 g.

CLICK 'N' CRIMP SETS

click 'n' crimp is available in standard sets, consisting of the crimping pliers body and the three most frequently used crimping profile inserts for a particular application:

CLICK 'N' CRIMP ELECTRICAL ENGINEERING, with crimping profile inserts:

CIMCO-item no. 10 6010 (for insulated cable lugs from 0.5 mm<sup>2</sup> to 6 mm<sup>2</sup>),  
CIMCO-item no. 10 6011 (for non-insulated cable lugs 0.5 mm<sup>2</sup> to 10 mm<sup>2</sup>) and  
CIMCO-item no. 10 6012 (for wire end ferrules from 0.5 mm<sup>2</sup> to 10 mm<sup>2</sup>)

	1	10 6000
--	---	---------

CLICK 'N' CRIMP AUTOMOTIVE, with crimping profile inserts:

with crimping profile inserts CIMCO-item no. 10 6010 (for insulated cable lugs from 0.5 mm<sup>2</sup> to 6 mm<sup>2</sup>),  
CIMCO-item no. 10 6011 (for non-insulated cable lugs 0.5 mm<sup>2</sup> to 10 mm<sup>2</sup>) and  
CIMCO-item no. 10 6013 (for blade receptacles and blade terminals with open crimping ears from 0.5 mm<sup>2</sup> to 6 mm<sup>2</sup>)

	1	10 6002
--	---	---------

CLICK 'N' CRIMP DATA NETWORK TECHNOLOGY, with crimping profile inserts:

with crimping profile inserts CIMCO-item no. 10 6015 (for BNC/TNC coaxial plug connectors),  
CIMCO-item no. 10 6017 (for unshielded 8-pole modular plugs) and CIMCO-item no. 10 6019  
(for shielded 8-pole modular plugs, CIMCO design and similar)

	1	10 6009
--	---	---------



CLICK 'N' CRIMP SOLAR TECHNOLOGY, with crimping profile inserts:

with crimping profile inserts CIMCO-item no. 10 6010 (for insulated cable lugs from 0.5 mm<sup>2</sup> to 6 mm<sup>2</sup>),  
CIMCO-item no. 10 6027 (for solar plug connectors type MC 3 from 2.5 mm<sup>2</sup> to 6 mm<sup>2</sup>) and  
CIMCO-item no. 10 6028 (for solar plug connectors type MC 4 from 2.5 mm<sup>2</sup> to 6 mm<sup>2</sup>)

	1	10 6052
--	---	---------

CLICK 'N' CRIMP CRIMPING PROFILE INSERTS

click 'n' crimp can be assembled according to the user's individual requirements:

click 'n' crimp crimping pliers bodies without crimping profile inserts

	1	10 6005
--	---	---------

click 'n' crimp crimping profile inserts (in pairs, consisting of upper and lower profile jaw)  
for insulated cable lugs red – blue – yellow from 0.5 mm<sup>2</sup> to 6 mm<sup>2</sup> resp. AWG 22 to AWG 10, oval crimp (W)

<b>IS</b>	1 Pair	10 6010
-----------	--------	---------

for non-insulated cable lugs from 0.5 mm<sup>2</sup> to 10 mm<sup>2</sup> or AWG 22 to AWG 8, indent crimp (N)

<b>Q</b> <b>R</b>	1 Pair	10 6011
-------------------	--------	---------

for insulated and non-insulated wire end ferrules from 0.5 mm<sup>2</sup> to 10 mm<sup>2</sup> respectively AWG 22 to AWG 8, trapezoid crimp (B)

<b>ZAE</b> <b>AE</b>	1 Pair	10 6012
----------------------	--------	---------

for insulated and non-insulated wire end ferrules from 16 mm<sup>2</sup> to 35 mm<sup>2</sup> respectively AWG 5 to AWG 2, trapezoid-indent crimp (D2), optimised crimp shape; particularly suitable for thinned-out, finely-stranded conductors according to IEC 228

<b>ZAE</b> <b>AE</b>	1 Pair	10 6014
----------------------	--------	---------

for insulated and non-insulated wire end ferrules 25 mm<sup>2</sup> and 50 mm<sup>2</sup>, trapezoid-indent crimp (D1), optimised crimp shape; particularly suitable for thinned-out, finely-stranded conductors according to IEC 228

<b>ZAE</b> <b>AE</b>	1 Pair	10 6071
----------------------	--------	---------



Design	Size mm	PU	CIMCO-item no.
--------	---------	----	----------------

for non-insulated blade terminals and blade receptacles with open crimping ears from 0.5 mm<sup>2</sup> to 6 mm<sup>2</sup> resp. AWG 22 to AWG 10, roll crimp (C)

	FL	1 Pair	10 6013
--	----	--------	---------

for BNC/TNC coaxial plug connectors RG 58, RG 59, RG 62 AU, RG 174, hexagonal crimping (A)  
(crimping dimensions: 1.73 mm / 0.068" – 4.75 mm / 0.187" – 5.41 mm / 0.213" – 6.48 mm / 0.255")

		1 Pair	10 6015
--	--	--------	---------

for unshielded 6-pin modular plugs (Western plugs) RJ 11 (6P4C) and RJ 12 (6P6C), SS design, AMP (M4)

		1 Pair	10 6016
--	--	--------	---------

for unshielded 8-pin modular plugs (Western plugs) RJ 45 (8P8C), SS design, AMP (M5)

		1 Pair	10 6017
--	--	--------	---------

for shielded 8-pin modular plugs (Western plugs) RJ 45 (8P8C) CAT 5 etc., CIMCO design (M2)

		1 Pair	10 6019
--	--	--------	---------

for shielded 8-pin modular plugs (Western plugs) RJ 45 (8P8C) CAT 5 etc., HIROSE TM 11/21 design (M1)


		1 Pair	10 6018
--	--	--------	---------

for solar plug connectors type MC 3 from 2.5 mm<sup>2</sup> to 6 mm<sup>2</sup> (C3)

		1 Pair	10 6027
--	--	--------	---------

for solar plug connectors type MC 4 from 2.5 mm<sup>2</sup> to 6 mm<sup>2</sup> (C4)

		1 Pair	10 6028
--	--	--------	---------



## ONE-HAND SYSTEM CRIMPING PLIERS

Compound leverage crimping pliers with ratchet mechanism and pressure point release, with a variety of interchangeable crimping profile inserts fixed by two fastening screws. The ergonomically shaped crimping pliers are easy and convenient to use. The lever action of the handle triggers the integrated automatic ratchet mechanism. Adjustable automatic release guarantees optimum crimping results. All inserts are made of carbon tool steel. The 17 different profiles are suitable for almost all kinds of cable connector crimping.

PROFI-CRIMP tool body		1	10 6112
-----------------------	--	---	---------

Crimping profile inserts for insulated cable lugs according to DIN: 0.5 to 1 (red), 1.5 to 2.5 (blue), 4 to 6 mm<sup>2</sup> (yellow), AWG: 18/20 - 14/16 - 10/12, with oval crimp

Crimping pliers complete with insert	230	1	10 6144
Crimping profile inserts loose asymmetric, standard crimping	IS	1 Pair	10 2008
Crimping pliers complete with insert		1	10 1916
Crimping profile inserts loose symmetric, oval crimp	IS	1 Pair	10 2004

Crimping profile inserts for non-insulated cable lugs according to DIN: 1.5 to 10 mm<sup>2</sup>, AWG: 20 to 8

Crimping pliers complete with insert	230	1	10 6134
Crimping profile inserts loose, indent crimp	Q R	1 Pair	10 2003

Crimping profile inserts for non-insulated plug connectors with open crimping ears according to DIN: 0.5 to 1, 1.5 to 2.5, 4 to 6 mm<sup>2</sup>, AWG: 18/20 - 14/16 - 10/12

Crimping pliers complete with insert	230	1	10 6136
Crimping profile inserts loose, roll crimp	FL	1 Pair	10 2002

Crimping profile inserts for insulated plug connectors with open crimping ears with lateral conductor connection: 0.5 to 1, 1.5 to 2.5, AWG: 18/22 - 14/16

Crimping pliers complete with insert	220	1	10 6128
Crimping profile inserts loose, roll crimp		1 Pair	10 2016

Crimping profile inserts for non-insulated plug connectors with open crimping ears with lateral conductor connection: 0.5 to 1, 1.5 to 2.5, AWG: 18/22 - 14/16

Crimping pliers complete with insert	220	1	10 6130
Crimping profile inserts loose, roll crimp		1 Pair	10 2017

