





# **TECHNICAL INFORMATION**

| Watts:                 | 40                  |
|------------------------|---------------------|
| Lumens:                | 4000                |
| Shape:                 | Rectangle           |
| Input Power:           | AC:200-240V,50/60Hz |
| Long Life:             | 20,000 Hours        |
| Unit Color:            | White               |
| Body Type:             | FE + PP             |
| PF:                    | >0.9                |
| LED Chip Type:         | SMD                 |
| CRI:                   | >80                 |
| Operation Temperature: | -20°C to +40°C      |
| Dimmable:              | No                  |
| Beam Angle:            | 120°                |
| Color Temperature:     | 4000K               |
| Dimension:             | 1195x295x29mm       |
| Output Voltage:        | DC:410-453V         |
|                        |                     |











## **FEATURES**

- 2in1 Recessed and Surfaced installation
- Powerful LED light source with lumen efficeincy of 100LM/W
- Strong and sturdy FE + PP Body
- Easy to Install and No UV radiation
- High quality power driver
- Suitable for offices, conference rooms, showrooms, lobbies, cabins, hospitals etc





V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide an extended multi-year warranty on our products, as well as detailed support.

One brand, endless solutions..

SKU: 6625 - 1410 940 View more details



# **PACKAGING**

Gross Weight (Kgs): 2.68 Unit CBM: 0.018469 Dimension: 1195x295x29mm

#### MASTER BOX PACKAGING

Box Qty: Qty Per Pallet: 10

## LISTING DETAILS

Ean Code: 3800157662024