



### TECHNICAL INFORMATION

|                       |                    |
|-----------------------|--------------------|
| Watts                 | 400                |
| Lumens                | 48000              |
| Input Power           | AC:220-240V, 50Hz  |
| Long Life             | 30,000 Hours       |
| Unit Color            | Black              |
| Body Type             | Die-Cast Aluminium |
| PF                    | >0.9               |
| LED Chip Type         | SMD-Samsung Chip   |
| CRI                   | >70                |
| Operation Temperature | -20°C to +45°C     |
| Dimmable              | No                 |
| Beam Angle            | 100°               |
| Color                 | 4000K              |
| Dimension             | 580x505x155mm      |
| lumens per watt       | 120                |
| LED Chip Solution     | 9V 100mA           |

### 120LM SLIMLINE PRO

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide extended multi-year warranty on our products, as well as detailed support.

*One brand, endless solutions..*

SKU: 964 - 1402 938

[View more details](#)



### FEATURES

- Perfect replacement for Metal Halide Floodlights, High Pressure Sodium Floodlights and Halogen Floodlights
- Product designed with high lumen efficiency of 120 LM/W
- High quality LED SMD-Samsung Chip chip and high power driver
- Fascia glass sealed with Silicone Rubber for superior waterproof /airtight performance
- Constant current Integrated IC driver - Built in driver - no external power supply required
- Built Strong and durable with Die-Cast Aluminium - Corrosion resistant design
- Suitable for building facades, sports facilities, industrial, commercial billboards, hoardings, parking lots etc.
- Recommended daily usage: 10 - 12 hours \*Exceeding recommended daily usage will void warranty

### PACKAGING

Gross Weight: 15.45  
Unit CBM: 0.0826  
Dimension: 580x505x155mm

### MASTER BOX PACKAGING

Box Qty: 1

### LISTING DETAILS

Commodity Code: 9405403990  
EanCode: 3800157649728

CE/EMC

CE/LVD

