



www.vtacexports.com







TECHNICAL INFORMATION

Watts:	29
Lumens:	3480
Input Power:	AC:200-240V, 50/60Hz
Long Life:	30,000 Hours
Unit Color:	White
Body Type:	Aluminium + PMMA + PP
PF:	>0.9
LED Chip Type:	SMD-Samsung Chip
CRI:	>80
Operation Temperature:	-20°C to +40°C
Dimmable:	No
Beam Angle:	120°
Color:	6400K
Dimension:	595x595x14mm
Output Voltage:	DC:30-42V
Input Current :	0.25A



FEATURES

- Powerful LED light source with lumen efficeincy of LM/W
- Strong and sturdy Aluminium + PMMA + PP body
- panel designed to meet European standards
- Fitted with high efficiency SMD-Samsung Chip LED Chips that offer up to 80% in energy savings
- Higher light transmission rate
- Easy to connect driver for quicker isntallation
- High quality power driver ensures reliable lifetime
- Controlled Glare rating for comfortable commercial application
- Suitable for offices, conference rooms, showrooms, lobbies, cabins, kitchens etc.
- Recommended daily usage: 10 12 hours *Exceeding recommended daily usage will void warrantyy




PRO 60X60 | LED LIGHTING

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide extended multi-year warranty on our products, as well as detailed support.

One brand, endless solutions..

SKU: 20048 - 1563 940 View more details







PACKAGING

Gross Weight: 18 Unit CBM: 0.05565625 Dimension: 595x595x14mm

MASTER BOX PACKAGING

Box Qty:	1
Qty Per Pallet:	22
Length (Box) mm:	130
Width (Box) mm:	625
Height (Box) mm:	685

LISTING DETAILS

Commodity Code: 9405403990 EanCode: 3800157655415