

Baterie litowe 3,6V Tadiran



Producent	TADIRAN
Napięcie znamionowe	3,6V
Bateria	litowa (LTC)
Wyprowadzenia	brak

Symbol	Rozmiar	Pojemność [mAh]	Wymiary zewn. [mm]	Prąd znam. [mA]	Prąd maks. [mA]	Prąd imp. maks. [mA]
SL-2770/S	C, R14	8500	Ø26,2x50	3	100	300
SL-2780/S	D, R20	19000	Ø32,9x61,5	4	340	280
SL-2790/S	DD	35000	Ø32,9x123,5	10	450	1000
SL-350/S	1/2AA	1200	Ø14,7x25,2	0,6	6	-
SL-360/S	AA, R6	2400	Ø14,7x50,5	2	20	-
SL-361/S	2/3AA	1600	Ø14,7x33,5	1	10	-
SL-550/S	1/2AA	900	Ø14,7x25,2	0,6	50	100
SL-560/S	AA, R6	1800	Ø14,7x50,5	2	100	200
SL-561/S	2/3AA, 2/3R6	1100	Ø14,7x33,5	1	75	150
SL-750/S	1/2AA, 1/2R6	1100	Ø14,7x25,2	1	50	100
SL-760/S	AA, R6	2200	Ø14,7x50,5	2	100	200
SL-761/S	2/3AA, 2/3R6	1500	Ø14,7x33,5	1,3	75	150

SL-860/S	AA, R6	2400	Ø14,7x50,5	1	60	120
SL-861/S	2/3AA, 2/3R6	1600	Ø14,7x33,5	0,5	30	75

Właściwości:

- nieładowna
- wysokotemperaturowa (**SL-5xx/S**)

Temperatura pracy:

- -55...85°C (**SL-27x0/S**, **SL-3xx/S**, **SL-7xx/S**, [SL-860/S](#), [SL-861/S](#))
- -55...130°C (**SL-5xx/S**)

Zarządzanie opisem produktu: www.parcat.eu