



⊖ płaski

320N

Nr zam.	⊖	mm	mm	mm	mm	mm
00819	2,0	60	0,4	164	23	10
00820	2,5	75	0,4	179	23	10
00821	3,0	100	0,5	204	23	10
00822	3,5	100	0,6	204	23	10
00823	4,0	100	0,8	211	30	10
00824	4,5•	125	1,0	236	30	10
00825	4,5•	175	1,0	286	30	5
31863	4,5	200	1,0	311	30	5
00826	5,5	125	1,0	243	36	10
00827	5,5•	175	1,0	293	36	5
00828	6,0•	150	1,2	268	36	10
00829	6,5	150	1,2	268	36	10
00830	8,0	175	1,2	299	41	10
00831	8,0	175	1,6	299	41	10
00832	10,0•	200	1,6	324	41	5

• Dodatkowy rozmiar. Poza normą DIN.
Produktowany zgodnie z IEC 60900.

⊕ Phillips

321N

Nr zam.	⊕	mm	mm	mm	mm	mm
00846	PH0	60	164	23		10
00847	PH1	80	191	30		10
00848	PH2	100	218	36		10
00849	PH3	150	268	41		10
00850	PH4	200	318	41		5

Produktowany zgodnie z IEC 60900.

⊕ Pozidriv

324

Nr zam.	⊕	mm	mm	mm	mm	mm
00877	PZ0	60	164	23		10
00878	PZ1	80	191	30		10
00879	PZ2	100	218	36		10
00880	PZ3	150	324	41		5

Produktowany zgodnie z IEC 60900.

⊕ PlusMinus/Phillips

327

Nr zam.	⊕	mm	mm	mm	mm	mm
30716	SL/PH1	80	191	30		10
30715	SL/PH2	100	218	36		10

Produktowany zgodnie z IEC 60900.

⊕ PlusMinus/Pozidriv

328

Nr zam.	⊕	mm	mm	mm	mm	mm
30700	SL/PZ1	80	191	30		10
30701	SL/PZ2	100	218	36		10

Produktowany zgodnie z IEC 60900.

⊕ TORX®

325

Nr zam.	⊕	mm	mm	mm	mm	mm
03760	T5	60	164	23		10
03761	T6	60	164	23		10
03762	T7	60	164	23		10
00881	T8	60	164	23		10
00882	T9	60	164	23		10

Produktowany zgodnie z IEC 60900.

⊕ sześciokątny

323N

Nr zam.	⊕	mm	mm	mm	mm	mm
30361	2,5	75	179	23		10
30362	3,0	75	179	23		10
30363	4,0	75	186	30		10
30364	5,0	75	186	30		10
30365	6,0	100	218	36		10
30366	8,0	100	218	36		10

Produktowany zgodnie z IEC 60900.

⊕ czworokątny

358N

Nr zam.	⊕	mm	mm	mm	mm	mm
32396	#1	2,3	100	211	30	10
32397	#2	2,8	150	268	36	10

Produktowany zgodnie z IEC 60900.