

Aparatura modułowa


1A

Wytaczniki instalacyjne

serii S200

6000

B



S200 Charakterystyka B

Zgodność z normami: IEC/EN 60898, IEC/EN 60947-2

Icn = 6 kA

Liczba biegunów	Prąd znamionowy In A	Typ	Kod zamówieniowy
1	6	S201-B6	2CDS251001R0065
	10	S201-B10	2CDS251001R0105
	13	S201-B13	2CDS251001R0135
	16	S201-B16	2CDS251001R0165
	20	S201-B20	2CDS251001R0205
	25	S201-B25	2CDS251001R0255
	32	S201-B32	2CDS251001R0325
	40	S201-B40	2CDS251001R0405
	50	S201-B50	2CDS251001R0505
	63	S201-B63	2CDS251001R0635
2	6	S202-B6	2CDS252001R0065
	10	S202-B10	2CDS252001R0105
	13	S202-B13	2CDS252001R0135
	16	S202-B16	2CDS252001R0165
	20	S202-B20	2CDS252001R0205
	25	S202-B25	2CDS252001R0255
	32	S202-B32	2CDS252001R0325
	40	S202-B40	2CDS252001R0405
	50	S202-B50	2CDS252001R0505
	63	S202-B63	2CDS252001R0635
3	6	S203-B6	2CDS253001R0065
	10	S203-B10	2CDS253001R0105
	13	S203-B13	2CDS253001R0135
	16	S203-B16	2CDS253001R0165
	20	S203-B20	2CDS253001R0205
	25	S203-B25	2CDS253001R0255
	32	S203-B32	2CDS253001R0325
	40	S203-B40	2CDS253001R0405
	50	S203-B50	2CDS253001R0505
	63	S203-B63	2CDS253001R0635
4	6	S204-B6	2CDS254001R0065
	10	S204-B10	2CDS254001R0105
	13	S204-B13	2CDS254001R0135
	16	S204-B16	2CDS254001R0165
	20	S204-B20	2CDS254001R0205
	25	S204-B25	2CDS254001R0255
	32	S204-B32	2CDS254001R0325
	40	S204-B40	2CDS254001R0405
	50	S204-B50	2CDS254001R0505
	63	S204-B63	2CDS254001R0635

U_{Bmax}

440 V ~

60 V ~

U_{Bmax}

440 V ~

125 V ~

U_{Bmax}

440 V ~

125 V ~

U_{Bmax}

440 V ~

125 V ~

* U_{Bmax} 125 V ~ z 2 biegunami połączonymi szeregowo

8

ABB