

1A

Wyłączniki instalacyjne

serii S200

6000

C





S200 Charakterystyka C

Zgodność z normami: IEC/EN 60898, IEC/EN 60947-2

I_{cn} = 6 kA

Liczba biegunów	Prąd znamionowy In A	Typ	Kod zamówieniowy
1	0,5	S201-C0,5	2CDS251001R0984
	1	S201-C1	2CDS251001R0014
	1,6	S201-C1,6	2CDS251001R0974
	2	S201-C2	2CDS251001R0024
	3	S201-C3	2CDS251001R0034
	4	S201-C4	2CDS251001R0044
	6	S201-C6	2CDS251001R0064
	8	S201-C8	2CDS251001R0084
	10	S201-C10	2CDS251001R0104
	13	S201-C13	2CDS251001R0134
	16	S201-C16	2CDS251001R0164
	20	S201-C20	2CDS251001R0204
	25	S201-C25	2CDS251001R0254
	32	S201-C32	2CDS251001R0324
	40	S201-C40	2CDS251001R0404
	50	S201-C50	2CDS251001R0504
	63	S201-C63	2CDS251001R0634
2	0,5	S202-C0,5	2CDS252001R0984
	1	S202-C1	2CDS252001R0014
	1,6	S202-C1,6	2CDS252001R0974
	2	S202-C2	2CDS252001R0024
	3	S202-C3	2CDS252001R0034
	4	S202-C4	2CDS252001R0044
	6	S202-C6	2CDS252001R0064
	8	S202-C8	2CDS252001R0084
	10	S202-C10	2CDS252001R0104
	13	S202-C13	2CDS252001R0134
	16	S202-C16	2CDS252001R0164
	20	S202-C20	2CDS252001R0204
	25	S202-C25	2CDS252001R0254
	32	S202-C32	2CDS252001R0324
	40	S202-C40	2CDS252001R0404
	50	S202-C50	2CDS252001R0504
	63	S202-C63	2CDS252001R0634
3	0,5	S203-C0,5	2CDS253001R0984
	1	S203-C1	2CDS253001R0014
	1,6	S203-C1,6	2CDS253001R0974
	2	S203-C2	2CDS253001R0024
	3	S203-C3	2CDS253001R0034
	4	S203-C4	2CDS253001R0044
	6	S203-C6	2CDS253001R0064
	8	S203-C8	2CDS253001R0084
	10	S203-C10	2CDS253001R0104
	13	S203-C13	2CDS253001R0134
	16	S203-C16	2CDS253001R0164
	20	S203-C20	2CDS253001R0204
	25	S203-C25	2CDS253001R0254
	32	S203-C32	2CDS253001R0324
	40	S203-C40	2CDS253001R0404
	50	S203-C50	2CDS253001R0504
	63	S203-C63	2CDS253001R0634

U_{Bmax}

440 V ~

60 V ~

U_{Bmax}

440 V ~

125 V ~

U_{Bmax}

440 V ~

440 V ~

* U_{Bmax} 125 V ~ z 2 biegunami połączonymi szeregowo