

Switch fuses, back in, back out connection

Rated op. current AC-20%23A ≤ 690V [A]	Rated op. power AC-23A 400/500/690V [kW]	Fuse size ¹⁾	Number of poles	Type	Order number	Weight [kg]
--	--	----------------------------	-----------------------	------	--------------	----------------

Mechanism between the poles

Including a black handle OHB65J6 with I-O and ON-OFF -indication (IP65) and a shaft OXP6X161 (length 161 mm). Includes a terminal bolt kit M8x25.

125	55/75/110	000,00	3	OS125D12BBW	1SCA022556R3630	1.9
125	55/75/110	000,00	4	OS125D22BBN2W	1SCA022558R8200	2.2
160	75/90/132	000,00	3	OS160D12BBW	1SCA022556R3550	1.9
160	75/90/132	000,00	4	OS160D22BBN2W	1SCA022558R8710	2.2

Including a black handle OHB125J12 with I-O and ON-OFF -indication (IP65) and a shaft OXP12X250 (length 250 mm). Includes a terminal bolt kit and an IP20 fuse cover.

250	132/160/200	0...1	3	OESA250D12BB	1SCA022270R6210	7.7
250	132/160/200	0...1	4	OESA250D22BBN2	1SCA022279R5130	8.6
400	200/250/355	0¼ 2	3	OESA400D12BB	1SCA022271R3930	8.7
400	200/250/355	0¼ 2	4	OESA400D22BBN2	1SCA022279R5720	9.8
630	355/450/560	3	3	OESA630D12BB	1SCA022272R0980	16.4
630	340/400/540	3	4	OESA630D22BBN2	1SCA022272R1520	25.0
800 ¹⁾	380/470/600	3	3	OESA800D12BB	1SCA022279R7690	18.4
800 ¹⁾	380/470/600	3	4	OESA800D22BBN2	1SCA022279R8230	28.0

Mechanism at the end of the switch fuse

Including a black handle OHB65J6 with I-O and ON-OFF -indication (IP65) and a shaft OXP6X161 (length 161 mm). Includes a terminal bolt kit M8x25.

125	55/75/110	000,00	3	OS125D03BBW	1SCA022556R3800	1.9
125	55/75/110	000,00	4	OS125D04BBN2W	1SCA022558R9270	2.2
160	75/90/132	000,00	3	OS160D03BBW	1SCA022556R3710	1.9
160	75/90/132	000,00	4	OS160D04BBN2W	1SCA022558R9860	2.2

Including a black handle OHB125J12 with I-O and ON-OFF -indication (IP65) and a shaft OXP12X250 (length 250 mm). Includes a terminal bolt kit and an IP20 fuse cover.

250	132/160/200	0...1	3	OESA250D03BB	1SCA022271R3690	7.7
250	132/160/200	0...1	4	OESA250D04BBN2	1SCA022272R8960	8.6
400	200/250/355	0¼ 2	3	OESA400D03BB	1SCA022271R6520	8.7
400	200/250/355	0¼ 2	4	OESA400D04BBN2	1SCA022274R4650	9.8
630	355/450/560	3	3	OESA630D03BB	1SCA022271R9110	16.4
630	355/450/560	3	4	OESA630D04BBN2	1SCA022271R9710	25.0
800 ¹⁾	400/500/710	3	3	OESA800D03BB	1SCA022272R3310	18.4
800 ¹⁾	400/500/710	3	4	OESA800D04BBN2	1SCA022272R3900	28.0