

Description		part no. Article no.
XI/OC • Compact I/O system for connection to XC100/200 Modular PLCs • XC100/200 expandable with up to 15 XI/OC modules • Optionally, screw terminals or spring-cage terminals for digital/analog modules • UL/CSA approvals		
	Digital modules	
	8 inputs, 24 V DC	XIOC-8DI 257891
	16 inputs, 24 V DC	XIOC-16DI 257892
	32 inputs, 24 V DC	XIOC-32DI 267411
	8 outputs, 24 V DC, 0.3 A	XIOC-8DO 257894
	12 relay outputs	XIOC-12DO-R 257897
	16 outputs, 24 V DC, 0.3 A	XIOC-16DO 257896
	16 outputs, 24 V DC, 0.8 A, short-circuit proof	XIOC-16DO-S 257895
	16 connections, 4 inputs, 12 freely parameterizable as inputs/outputs, 24 V DC outputs 0.5 A	XIOC--16DX 262322
	32 outputs, 24 V DC, 0.2 A	XIOC-32DO 267413
	Analog modules	
	Inputs 8 Inputs 4 - 20 mA	XIOC-8AI-I2 262549
	Inputs 8 voltage input 8 - 10 V	XIOC-8AI-U1 257899
	Inputs 8 voltage inputs, ±10 V	XIOC-8AI-U2 257900
	Inputs 4 inputs for temperature monitoring, Pt100/1000	XIOC-4T-PT 257901
	Inputs 4 inputs for thermocouples Type K, J, L, B, N, E, R, S, T	XIOC-4AI-T 289933
	Outputs 2 outputs ± 10 V	XIOC-2AO-U2 257904
	Outputs 2 Outputs 0 - 10 V, 2 Outputs 4 - 20 mA	XIOC-2AO-U1-2AO-I2 257902
	Outputs 4 Outputs 0 - 10 V	XIOC-4AO-U1 257903
	Combination modules, 2 inputs and 1 output, 0 - 10 V 1 ms conversion time	XIOC-2AI-1AO-U1 262409
	Combination modules, 2 inputs and 1 output, 0 - 10 V, 0 - 20 mA 1 ms conversion time, individual changeover	XIOC-2AI-1AO-U1-L1 281545
	Combination modules, 4 inputs and 2 outputs, 0 - 10 V 1 ms conversion time	XIOC-4AI-2AO-U1 262405
	Combination modules, 4 inputs and 2 outputs, 0 - 10 V, 0 - 20 mA 1 ms conversion time, individual changeover	XIOC-4AI-2AO-U1-I1 281544
	Counter modules	
	1 input up to 100 kHz, 24 V DC, 5 V DC, 2 digital transistor outputs, opto-isolated, 24 V DC 30 pole plug required for counter module	XIOC-1CNT-100KHZ 257906
	2 inputs up to 100 kHz, (24 V DC or 5 V diff), 4 digital transistor outputs, opto-coupled, 24 V DC 30 pole plug required for counter module	XIOC-2CNT-100KHZ 257907
	2 incremental encoders up to 400 kHz, 5 V DC, 2 analog outputs, ±10 V	XIOC-2CNT-2AO-INC 262417
	Communication modules	
	PROFIBUS-DP master module	XIOC-NET-DP-M 257908
	PROFIBUS DP slave module	XIOC-NET-DP-S 286419
	Suconet K master module	XIOC-NET-SK-M 289982
	Serial interface RS232C, RS485, RS422 Operating modes: transparent mode, MODBUS master/slave, SUCOM-A, Suconet-K slave	XIOC-SER 267191
	Serial interface RS232C, RS485, RS422 Operating modes: transparent mode, MODBUS master/slave, SUCOM-A, DNP3 protocol	XIOC-TC1 135265