



Product data sheet

3TH4244-0AP0



CONTACTOR RELAY 44E EN 50 011 4NO+4NC,
SCREW TERMINALS AC OPERATION AC 230/220V
50HZ,
276/264V 60HZ

General details:	
Size of the contactor	0
Control circuit:	
Type of voltage	AC
Control supply voltage	
• at 50 Hz / for AC / rated value / minimum	230 V
• at 50 Hz / for AC / rated value / maximum	230 V
• at 60 Hz / for AC / rated value / minimum	277 V
• at 60 Hz / for AC / rated value / maximum	277 V
Supply voltage frequency / for auxiliary and control current circuit / rated value / minimum	50 Hz
Supply voltage frequency / for auxiliary and control current circuit / rated value / maximum	60 Hz
Main circuit:	
Operating current / at AC-14 / at AC-15 / at 230 V / rated value	10 A
Auxiliary circuit:	
Identification number and letter for switching elements	44 E
Number of NC contacts / for auxiliary contact	4
• delayed switching	0

• asynchronous switching	0
Number of NO contacts / for auxiliary contact	4
• delayed switching	0
• asynchronous switching	0
Number of change-over switches / for auxiliary contact	0
Connection type:	
Design of the electrical connection / for auxiliary and control current circuit	screw-type terminals
Mechanical design:	
Type of fixing/fixation	screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
last change:	10/31/2006

Technical Assistance:	Telephone: +49 (0) 911-895-5900 (8 ⁰⁰ - 17 ⁰⁰ CET)
	Fax: +49 (0) 911-895-5907
	E-Mail: technical-assistance@siemens.com
	Internet: www.siemens.de/lowvoltage/technical-assistance