




Outgoers up to 630 A for NZM1 – 3 and incomers up to 1600 A for NZM4



Moeller FK4810-1143GB-INT




- Features:**
- Section height 2000 mm
 - Degree of protection IP31 or IP55
 - Protection class I
 - Opening angle
 - 180° with separate mounting– 170° with side-by-side installation¹⁾
 - Exchangeable door hinges
 - Component mounting area for outgoing:
 - IP31 1500 mm
 - IP55 1600 mm




Type Frames top/ bottom	Type Vertical profiles	Type Fitting kit for outgoing with circuit-breakers
Article no. for 1 kit	Article no. for 1 kit	Article no. for 1 kit
mm	mm	mm

Sections for rear dropper bar position up to form 2b, actuation behind component mounting door in section width (interchangeable connection and dropper bar / component mounting area), max. installation depth = 237 mm




600	425	200	600
	600	200	800
	425	400	800
	600	400	1000

XSFB0606 284235	XSFH20 284245	XSMFIT06 284255
XSFB0806 284238	XSFH20 284245	XSMFIT06 284255
XSFB0806 284238	XSFH20 284245	XSMFIT06 284255
XSFB1006 284241	XSFH20 284245	XSMFIT06 284255




Sections for rear dropper bar position up to form 4b, actuation external or behind component mounting door (interchangeable connection and dropper bar / component mounting area), max. installation depth = 191 mm (with cover plate max 122 mm)




600	425	200	600
	600	200	800
	425	400	800
	600	400	1000

XSFB0606 284235	XSFH20 284245	XSMFDT0406 284753
XSFB0806 284238	XSFH20 284245	XSMFDT0606 284754
XSFB0806 284238	XSFH20 284245	XSMFDT0406 284753
XSFB1006 284241	XSFH20 284245	XSMFDT0606 284754



Sections with rear cable connection area for rear dropper bar position up to form 4b, actuation external or behind component mounting door (interchangeable connection and dropper bar / component mounting area), max. installation depth = 191 mm (with cover plate max 122 mm)



600	425	–	425
	600	–	600

XSFB0406 284232	XSFH20 284245	XSMFRDT0406 284756
XSFB0606 284235	XSFH20 284245	XSMFRDT0606 284757


Notes

¹⁾ Order alternative hinge for 180° with side-by-side mounting, see page 11/2

Outgoers up to 630 A for NZM1 – 3 and incomers up to 1600 A for NZM4



Moeller FK4810-1143GB-INT



Type Component mounting section door in section width ²⁾ – Component mounting section door ³⁾	Type Cable coupling area door ²⁾	Type Back plate
IP31 Ventilated left	IP31 Ventilated right	IP55 Without apertures
IP55 transparent, design version	IP55 solid	IP31 Ventilated
Article no. 1 off each	Article no. 1 off each	Article no. 1 off each
Article no. 1 off each	Article no. 1 off each	Article no. 1 off each

XSDMLV2006 284210	XSDMRV2006 284219	XSDMC2006 284199	XSDMD2006 284204	–	XSWV2006 284361	XSWC2006 284356
XSDMLV2008 284211	XSDMRV2008 284220	XSDMC2008 284200	XSDMD2008 284701	–	XSWV2008 284362	XSWC2008 284357
XSDMLV2008 284211	XSDMRV2008 284220	XSDMC2008 284200	XSDMD2008 284701	–	XSWV2008 284362	XSWC2008 284357
XSDMLV2010 284212	XSDMRV2010 284221	XSDMC2010 284201	–	–	XSWV2010 284363	XSWC2010 284358

XSDFMLV2004 284188	XSDFMRV2004 284190	XSDFMC2004 284184	XSDFMD2004 284186	XSDFCC2002 284182	XSWV2006 284361	XSWC2006 284356
XSDFMLV2006 284189	XSDFMRV2006 284191	XSDFMC2006 284185	XSDFMD2006 284187	XSDFCC2002-1 284700	XSWV2008 284362	XSWC2008 284357
XSDFMLV2004 284188	XSDFMRV2004 284190	XSDFMC2004 284184	XSDFMD2004 284186	XSDFMC2004 284184	XSWV2008 284362	XSWC2008 284357
XSDFMLV2006 284189	XSDFMRV2006 284191	XSDFMC2006 284185	XSDFMD2006 284187	XSDFCC2004 284183	XSWV2010	XSWC2010

XSDMLV2004 284209	XSDMRV2004 284218	XSDMC2004 284198	XSDMD2004 284203	–	XSWV2004 284360	XSWC2004 284355
XSDMLV2006 284210	XSDMRV2006 284219	XSDMC2006 284199	XSDMD2006 284204	–	XSWV2006 284361	XSWC2006 284356

Notes

²⁾ Doors always required.

³⁾ Door optional, if installed devices are covered off by front surrounds; always required for IP55.