




Gniazdo wtyczkowe przenośne w obudowie IP44

Numer wyrobu	In	Un	Liczba styków	Stopień ochrony	Dławnice	Przyłączalność przewodów	a	b	c
2629-326	16 A	230 V~	2P+Z	IP44	B16	1,0-2,5 mm ²	114	66	53
2627-326	16 A	400 V~	3P+Z	IP44	B18,5	1,0-2,5 mm ²	120	71	59
2622-326	16 A	230/400 V~	3P+N+Z	IP44	B18,5	1,0-2,5 mm ²	120	82	66
2643-326	32 A	400 V~	3P+Z	IP44	B22	2,5-6,0 mm ²	137	82	70
2642-326	32 A	230/400 V~	3P+N+Z	IP44	B27	2,5-6,0 mm ²	148	94	77



Gniazdo wtyczkowe przenośne szybkozłączne w obudowie IP44

Numer wyrobu	In	Un	Liczba styków	Stopień ochrony	Przyłączalność przewodów	a	b	c
132	16 A	230V~	2P+Z	IP44	1,0-2,5 mm ²	139	75	56
2623-326	16 A	230/400 V~	3P+N+Z	IP44	1,0-2,5 mm ²	138	82	66
133	32 A	230V~	2P+Z	IP44	2,5-6,0 mm ²	152	93	64
2644-326	32 A	230/400 V~	3P+N+Z	IP44	2,5-6,0 mm ²	155	94	77



Gniazdo wtyczkowe przenośne w obudowie IP67

Numer wyrobu	In	Un	Liczba styków	Stopień ochrony	Przyłączalność przewodów	a	b	Dławnice
2624-337	16 A	230 V~	2P+Z	IP67	1,0-2,5 mm ²	138	68	P16
2626-337	16 A	230/400 V~	3P+N+Z	IP67	1,0-2,5 mm ²	150	85	P16
2646-337	32 A	230/400 V~	3P+N+Z	IP67	2,5-6,0 mm ²	180	98	P21
2666-337	63 A	230/400 V~	3P+N+Z	IP67	4,0-10,0 mm ²	220	107	P29

