




Gniazdo wtyczkowe tablicowe IP44



Numer wyrobu	In	Un	Liczba styków	Stopień ochrony	Przyłączalność przewodów	a	b	c	d	e	f	g	h	r
2622-620	16 A	230/400 V~	3P+N+Z	IP44	1,5-4,0 mm ²	36	57	60	75,5	91	80	2,5	4,5	34,5
2625-620	16 A	127V~	2P+Z	IP44	1,5-4,0 mm ²	29	46	50	64,5	77	67	4,5	4,5	25,0
2627-620	16 A	400 V~	3P+Z	IP44	1,5-4,0 mm ²	26	59	50	64,5	77	67	2,5	4,5	30,0
2629-620	16 A	230V~	2P+ Z	IP44	1,5-4,0 mm ²	29	46	50	64,5	77	67	4,5	4,5	25,0
143	32 A	230V~	2P+ Z	IP44	1,5-4,0 mm ²	48	45	58	73	87	72	-	4,5	30,0
2642-620	32 A	230/400 V~	3P+N+Z	IP44	2,5-10,0 mm ²	38	75	70	83	97	85	2,5	4,5	38,0
2643-620	32 A	400 V~	3P+Z	IP44	2,5-10,0 mm ²	37	65	60	75,5	91	80	2,5	4,5	35,0
152 proste	16 A	230V~	2P+ Z	IP44	1,5-4,0 mm ²	54	23	59,4	75	-	-	-	4,5	30,0
153 proste	32 A	230V~	2P+ Z	IP44	1,5-6,0 mm ²	65	27	59,4	75	-	-	-	4,5	30,0



Gniazdo wtyczkowe tablicowe IP67



Numer wyrobu	In	Un	Liczba styków	Stopień ochrony	Przyłączalność przewodów	a	b	c	d	e	f	g	h	r
2624-630	16 A	230V~	2P+Z	IP67	1,5-4,0 mm ²	48	44	65,0	77	50	67	4	3,8	25,0
2626-630	16 A	230/ 400V~	3P+N+ Z	IP67	1,5-4,0 mm ²	50	50	75,5	91	60	80	4	3,8	35,0
2646-630	32 A	230/ 400 V~	3P+N+Z	IP67	2,5-10,0 mm ²	60	55	80	97	70	85	5	3,8	37,5
2666-630	63 A	230/ 400 V~	3P+N+Z	IP67	6,0-25,0 mm ²	80	75	91	108	75	90	6	4,5	40



Gniazdo wtyczkowe podtynkowe IP44



Numer wyrobu	In	Un	Liczba styków	Stopień ochrony	Przyłączalność przewodów	a	b	c*	d	e	f*
2629-420	16 A	230V~	2P+ Z	IP44	1,5-4,0 mm ²	35	57	71	82	98	88
2627-420	16 A	400 V~	3P+Z	IP44	1,5-4,0 mm ²	35	57	71	82	98	88
2622-420	16 A	230/ 400 V~	3P+N+Z	IP44	1,5-4,0 mm ²	41	68	83	93	113	103
2643-420	32 A	400 V~	3P+Z	IP44	2,5-6,0 mm ²	47	67	83	93	113	103
2642-420	32 A	230/ 400 V~	3P+N+Z	IP44	2,5-6,0 mm ²	54	71	95	106	122	110

* wymiar otworu pod wyrób