





Wtyczka odbiornikowa w obudowie IP44



Numer wyrobu	In	Un	Liczba styków	Stopień ochrony	Przyłączalność przewodów	a	b	c	d	e	f	g
3622-220	16 A	230/400 V~	3P+N+Z	IP44	1,0-2,5 mm ²	130	80	85	70	70	5	80
3623-220	16 A	400 V~	3P+ Z	IP44	1,0-2,5 mm ²	130	80	80	70	70	5	80
3629-220	16 A	230 V~	2P+ Z	IP44	1,0-2,5 mm ²	118	80	75	70	70	5	80
113	32 A	230 V~	2P+ Z	IP44	2,5-6,0 mm ²	166	72	72	34 45	71	5	-
3642-220	32 A	230/400 V~	3P+N+Z	IP44	2,5-6,0 mm ²	155	90	100	80	80	5	90
3643-220	32 A	400 V~	3P+Z	IP44	2,5-6,0 mm ²	145	90	92	80	80	5	90




Wtyczka odbiornikowa w obudowie IP67



Numer wyrobu	In	Un	Liczba styków	Stopień ochrony	Przyłączalność przewodów	a	b	c	d	e	f	g
3624-230	16 A	230 V~	2P+Z	IP67	1,0-2,5 mm ²	118	80	84	70	70	5	80
3626-230	16 A	230/400 V~	3P+N+Z	IP67	1,0-2,5 mm ²	130	80	89	70	70	5	80
3646-230	32 A	230/400 V~	3P+N+Z	IP67	2,5-6,0 mm ²	155	90	108	80	80	5	90



Wtyczka kątowa w obudowie IP44



Numer wyrobu	In	Un	Liczba styków	Stopień ochrony	Wielkość dławicy	Przyłączalność przewodów	a	b
3629-724	16 A	230 V~	2P+Z	IP44	P16	1,0-2,5 mm ²	110	86
3623-724	16 A	400 V~	3P+ Z	IP44	P21	1,0-2,5 mm ²	112	98
3622-724	16 A	230/400 V~	3P+N+Z	IP44	P21	1,0-2,5 mm ²	116	105
3643-724	32 A	400 V~	3P+Z	IP44	P21	2,5-6,0 mm ²	130	110
3642-724	32 A	230/400 V~	3P+N+Z	IP44	P29	2,5-6,0 mm ²	145	128