




## K 0400

### empty box

- with transparent lid
- lid fasteners for tool operation
- box walls without knockouts
- please order DIN rails or mounting plates additionally



Dimension drawing



|                         |                                      |
|-------------------------|--------------------------------------|
| rated current:          | for built-in equipment bis 63 A<br>A |
| degree of protection:   | IP 65                                |
| mounting width          | 275 mm                               |
| mounting height         | 575 mm                               |
| material:               | thermoplastic                        |
| max. installation depth | with built-in mounting plate 146 mm  |
| colour:                 | grey RAL 7035                        |

#### Operating and ambient conditions

|                                                           |                                                                                                                                                                                                                                                                           |
|-----------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Application area                                          | Suitable for indoor installation and outdoor installation, protected against weather influences according to DIN VDE 0100 Part 737                                                                                                                                        |
| ambient temperature                                       | Maximum value + 40° C<br>Minimum value - 25° C                                                                                                                                                                                                                            |
| Fire protection in the event of internal faults           | Demands placed on electrical devices from standards and laws Minimum requirements - Glow wire test in accordance with IEC 60 695-2-11: - 650°C for boxes and cable glands - 850°C for parts of insulating material necessary to retain current carrying parts in position |
| Fire protection in the event of specific risks or hazards | Demands placed on electrical devices from standards and laws Minimum requirements - Glow wire test in accordance with IEC 60 695-2-11: - 650°C for boxes and cable glands - 850°C for parts of insulating material necessary to retain current carrying parts in position |
| Burning behaviour                                         | Glow wire test IEC 60 695-2-11: 750° C<br>UL Subject 94 V-2<br>flame resistant self-extinguishing                                                                                                                                                                         |
| degree of protection against mechanical load              | IK07 (2 Joule)                                                                                                                                                                                                                                                            |
| Toxic behaviour                                           | halogen-free silicone-free "halogen-free" in accordance with the examination of the cables and insulated wires - corrosiveness of fumes - as per IEC 754-2                                                                                                                |
| Note:                                                     | To material properties see technical data.                                                                                                                                                                                                                                |