


Odgałęźniki izolacyjne cztero i pięciorowe



Numer wyrobu	Parametry	Stopień ochrony	Przyłączalność przewodów	Dławnice	a	b	c
5271-200	4t x 25,0 mm ²	IP44	10,0 - 25,0 mm ²	2 x B25 wewnątrz	165	165	95
5231-627	5t x 4,0 mm ²	IP44	1,0 - 4,0 mm ²	4 x B16,5 wewnątrz	100	100	53
5251-627	5t x 10,0 mm ²	IP44	2,5 - 10,0 mm ²	4 x B25 wewnątrz	130	130	68
5273-200	5 x (25 mm ² + 4x10 mm ²)	IP44	5x(10,0 - 25,0 mm ² + 4x4-10 mm ²)	2 x B25 wewnątrz	165	165	95
039	5t x 25/10 mm ²	IP44	6,0 - 25,0 mm ²	2 x D25 lub 2 x D16,5	166	166	100
042	5t x 2,5 mm ²	IP44	1,0 - 2,5 mm ²	4xD13,5	106	95	38

Odgałęźniki metalowe IP55

Numer wyrobu	Parametry	Stopień ochrony	Przyłączalność przewodów	Liczba otworów wlotowych	Wielkość otworów wlotowych	a	b	c
5123-201 / 016	5t x 1-2,5 mm ²	IP55	1,0 - 2,5 mm ²	2	P11	110	110	42
5123-301 / 017	5t x 1-2,5 mm ²	IP55	1,0 - 2,5 mm ²	3	P11	110	110	42
5123-401 / 018	5t x 1-2,5 mm ²	IP55	1,0 - 2,5 mm ²	4	P11	110	110	42
5133-202 / 014	5t x 4 mm ²	IP55	1,0 - 4,0 mm ²	2	P13,5	110	110	42
5133-203 / 019	5t x 4 mm ²	IP55	1,0 - 4,0 mm ²	2	P16	110	110	42
5133-302 / 015	5t x 4 mm ²	IP55	1,0 - 4,0 mm ²	3	P13,5	110	110	42
5133-303 / 020	5t x 4 mm ²	IP55	1,0 - 4,0 mm ²	3	P16	110	110	42
5133-402 / 013	5t x 4 mm ²	IP55	1,0 - 4,0 mm ²	4	P13,5	110	110	42
5133-403 / 021	5t x 4 mm ²	IP55	1,0 - 4,0 mm ²	4	P16	110	110	42
5143-203 / 022	5t x 2,5-6 mm ²	IP55	2,5-6 mm ²	2	P16	136	156	54
5143-303 / 023	5t x 2,5-6 mm ²	IP55	2,5-6 mm ²	3	P16	136	156	54
5143-403 / 024	5t x 2,5-6 mm ²	IP55	2,5-6 mm ²	4	P16	136	156	54
5153-204 / 025	5t x 10,0 mm ²	IP55	2,5 - 10,0 mm ²	2	P21	136	156	54
5153-304 / 026	5t x 10,0 mm ²	IP55	2,5 - 10,0 mm ²	3	P21	136	156	54
5153-404 / 027	5t x 10,0 mm ²	IP55	2,5 - 10,0 mm ²	4	P21	136	156	54
5163-225 / 068/I	5t x 16,0 mm ²	IP55	6,0 - 16,0 mm ²	2	P29	181	211	76
5163-226 / 068/IV	5t x 16,0 mm ²	IP55	6,0 - 16,0 mm ²	2	P36	187	217	76
5163-325 / 068/II	5t x 16,0 mm ²	IP55	6,0 - 16,0 mm ²	3	P29	181	211	76
5163-326 / 068/V	5t x 16,0 mm ²	IP55	6,0 - 16,0 mm ²	3	P36	187	217	76
5163-425 / 068/III	5t x 16,0 mm ²	IP55	6,0 - 16,0 mm ²	4	P29	181	211	76
5163-426 / 068/VI	5t x 16,0 mm ²	IP55	6,0 - 16,0 mm ²	4	P36	187	217	76