

Amp.	Bieguny	Pakowane po / szt.	110V~ 50/60Hz 4h	230V~ 50/60Hz 3p=6h 4p+5p=9h	400V~ 50/60Hz 3p=9h 4p+5p=6h	500V~ 50/60Hz 7h	440V~ 60Hz 3h
			Nr kat.	Nr kat.	Nr kat.	Nr kat.	Nr kat.
16	3	1	7513-4	7513-6	7513-9	7513-7	
16	4	1	7514-4	7514-9	7514-6	7514-7	
16	5	1	7515-4	7515-9	7515-6	7515-7	
32	3	1	7523-4	7523-6	7523-9	7523-7	
32	4	1	7524-4	7524-9	7524-6	7524-7	
32	5	1	7525-4	7525-9	7525-6	7525-7	



7525-6

16	3	1	75132-4	75132-6	75132-9	75132-7	
16	4	1	75142-4	75142-9	75142-6	75142-7	
16	5	1	75152-4	75152-9	75152-6	75152-7	
32	3	1	75232-4	75232-6	75232-9	75232-7	
32	4	1	75242-4	75242-9	75242-6	75242-7	75242-3
32	5	1	75252-4	75252-9	75252-6	75252-7	



75252-6



■ ■ ■ Dane techniczne:

- gniazda z rozłącznikiem i blokadą mechaniczną w wersji tablicowej i stałej
- 16A i 32A 3-, 4- i 5 biegunowe
- IP44 i IP67
- rozłącznik 0-1 PCE-Merz MLO; EN 60947-3; AC22A, 10kA
- duża przestrzeń montażowa
- obudowa wykonana z odpornego na uderzenia termoplastycznego tworzywa
- wykonanie zgodne z normą EN60309, ÖVE