

UNI-T®

UT118 SERIES

Pen Type Digital Multimeters

UT118A/UT118B



EN 61010-1
EN 61326-1



■ UT118A



■ UT118B

SPECIFICATIONS

Specifications	Range		Best Accuracy	
Model	SCAN Mode	AUTO Mode	UT118A	UT118B
DC Voltage(V)	3V/30V/300V	3V/30V/300V	±(1%+3)	±(1%+3)
AC Voltage(V)	3V/30V/300V	3V/30V/300V	±(1%+4)	±(1%+4)
Resistance(Ω)	300Ω/3kΩ/30kΩ/300kΩ/3MΩ	300Ω/3kΩ/30kΩ/300kΩ/3MΩ/30MΩ	±(1%+3)	±(1%+3)
Capacitance (F)	3nF/30nF/300nF/3μF/30μF/300μF	3nF/30nF/300nF/3μF/30μF/300μF/3mF	±(3%+5)	±(3%+5)

Features				
Display Count			3000	3000
Auto Range			✓	✓
EF Function				✓
Diode			✓	✓
Auto Power Off	Around 10 Minutes		✓	✓
Continuity Buzzer			✓	✓
Low Battery Indication			✓	✓
Data Hold			✓	✓
MAX Mode			✓	✓
MIN Mode			✓	✓
LCD Backlight			✓	✓
Penlight			✓	✓
Input Impedance for DCV	≥10MΩ		✓	✓

GENERAL CHARACTERISTICS

Power	3V Li-MnO2 Cion Cell Battery
LCD Size	28mm×14mm
Product Color	Red and Grey
Product Net Weight	90 g
Product Size	20mm×27mm×182mm
Standard Accessories	Battery, Test Lead
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	80 PCs
Standard Carton Measurement	570mm×300mm×415mm (0.071 CBM Per Export Carton)
Standard Carton Gross Weight	12.5 Kg