

UNI-T®

UT15 SERIES **Waterproof Type Voltage Testers** UT15A ■ UT15B ■ UT15C



EN:61010-1
 EN:61326-1
 EN:61243-3



■ UT15A



UT15B ■



■ UT15C

SPECIFICATIONS

Specifications	Range	Best Accuracy		
Model		UT15A	UT15B	UT15C
LED AC/DC Voltage Indication (V)	12V	0~12V	0~12V	0~12V
	24V	19V±2V	19V±2V	19V±2V
	50V	48V±6V	48V±6V	48V±6V
	120V	110V±20V	110V±20V	110V±20V
	230V	200V±20V	200V±20V	200V±20V
	400V	340V±30V	340V±30V	340V±30V
	690V	520V±30V	520V±30V	520V±30V
Phase Rotation Test	Operating Voltage: 0V~690V Frequency: 50Hz~60Hz	✓	✓	✓
Single Lead(L2)Voltage Detection	Operating Voltage: 0V~690V Frequency: 50Hz~400Hz	✓	✓	✓
Continuity Test	Resistance: 0~100KΩ Beeper and LED Light Indicator		✓	✓
Polarity Detection	Positive & Negative	✓	✓	✓
Features				
Water-Proof (IP65)		✓	✓	✓
Auto Range		✓	✓	✓
Work Light		✓	✓	✓
Low Battery Indication	Short circuit two leads, LED and beeper off when the battery is low	✓	✓	✓
LCD AC/DC Voltage Display	24V~690V			±(3%+5)

GENERAL CHARACTERISTICS

Power	1.5V Batteries (R03)×2
LCD Size	UT15C-23mm × 12mm
Product Color	Red and Grey
Product Net Weight	210g
Product Size	275mm × 51mm × 30mm
Standard Accessories	Batteries
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	30PCs
Standard Carton Measurement	440mm × 295mm × 455mm (0.079 CBM Per Standard Carton)
Standard Carton Gross Weight	17Kg