

UNI-T®

UT256 SERIES
200A True RMS Fork Meters
UT256B

NEW



UL61010-1
EN61010-1
EN61010-2-032
EN61010-2-033
EN61326-1



■ **UT256B**

SPECIFICATIONS



Specifications	Range	Best Accuracy
Model		UT256B
AC Current (A)	200A	±(2.5%+5)
DC Current (A)	200A	±(2.5%+5)
AC Voltage(V)	6V/60V/600V/750V	±(1.2%+3)
DC Voltage(V)	600mV/6V/60V/600V/1000V	±(0.8%+3)
Resistance (Ω)	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(1.0%+2)
Capacitance (F)	60nF/600nF/6μF/60μF/600μF/6mF/60mF	±(4%+20)
Features		
Display Count		6000
Auto Range		✓
True RMS		✓
Diode	Around 3.0V	✓
NCV		✓
Data Hold		✓
Zero Mode		✓
Relative Mode		✓
LCD Backlight		✓
Auto Power Off	Around 15 Minutes	✓
Continuity Buzzer		✓
Low Battery Indication	≤2.4V	✓
Input Protection		✓
Input Impedance for DCV	≥10MΩ	✓

GENERAL CHARACTERISTICS

Power	AAA 1.5V x 2
LCD Size	36.5mm x 24mm
Product Color	Red and Grey
Product Net Weight	163.7g
Product Size	210mm x 53mm x 35mm
Standard Accessories	Batteries, Test Lead
Standard Individual Packing	Gift Box, Carrying Bag, English Manual
Standard Quantity Per Carton	40PCs
Standard Carton Measurement	490mm x 350 mm x 305mm (0.052 CBM Per Standard Carton)
Standard Carton Gross Weight	15.2Kg