



*Saves Your Energy*

PRODUCT CARD

9/9/16

## SP15

### Insulating cover

Code	SP15
GTIN	6418677405211
Name	Insulating cover MAX 150 mm <sup>2</sup>
Description	SP15 is used as a connector cover. The cover has to be installed so that the drain hole for ambient water is downwards. The cover is made of UV-radiation and weather resistant thermoplastic. Suitable for SM2.1, SM2.11, SM2.2, SM2.21, SM2.25, SL4.2, SL4.21, SL4.25, SL4.26, SL37.1, SL37.2, SL39.2



## Technical specification

### Dimensions

Weight:	0.03 kg
Conductor size max.:	150 mm <sup>2</sup>

### Electrical values

Test voltage:	4 kV / 50 Hz / 1 min
---------------	----------------------

### Features

For connector:	SM2.xx, SL3.xx, SL4.xx, SL37.xx, SL39.xx
----------------	--

### Ratings

ETIM class:	EC000437
-------------	----------

### Specification

Use:	The cover is used with Al/Al and Al/Cu connectors as insulation and to protect the connectors against corrosion caused by climatic conditions.
Construction:	The cover is made of weather and UV-radiation resistant special black plastic.
Installation:	After installation of connector cut off necessary caps for conductors and attach the plastic cover on the connector. Be sure that

<b>Tools required:</b>	Knife
<b>Markings:</b>	SP 15, Ensto
<b>Standard:</b>	SFS 4644

## ETIM

---

### ETIM

<b>Width:</b>	58 mm
<b>Height:</b>	71.5 mm
<b>Material housing:</b>	Plastic
<b>UV resistant:</b>	1
<b>With hinged lid:</b>	1
<b>Shape:</b>	Rectangular
<b>Type of housing:</b>	Socket case
<b>Position cable feed:</b>	Two-sided
<b>Coating housing:</b>	Uncoated
<b>Locking mechanism:</b>	Push Pull
<b>Corrosion resistant:</b>	1

## Packaging

---

### Default package

<b>Size:</b>	100
<b>Length:</b>	400 mm
<b>Width:</b>	400 mm
<b>Height:</b>	330 mm
<b>Weight (net):</b>	3.1 kg
<b>Volume:</b>	0.0528

### Pallet package

<b>Size:</b>	1800
<b>Length:</b>	1200 mm
<b>Width:</b>	800 mm
<b>Height:</b>	1150 mm
<b>Weight (net):</b>	55.8 kg
<b>Weight (brt):</b>	76 kg
<b>Volume:</b>	1.104