



Saves Your Energy

PRODUCT CARD

09.09.2016

SEW20.3

Zacisk ochrony przeciwłukowej

Typ	SEW20.3
GTIN	6438100305581
Nazwa	Zacisk ochrony przeciwłukowej Z rożkiem do uziemień, Al 35-157mm ²
Opis	Stosowany do ochrony przeciwłukowej linii PAS. Podczas montażu nie ma potrzeby zdejmowania izolacji z przewodu. Rożek ten jest specjalnie dostosowany do zakładania na nim uziemiaczy przenośnych z zaciskiem śrubowym. Zacisk przebijający izolację posiada miejsce do przyłączenia przewodu Al owiniętego wokół szyjki izolatora.



Specyfikacje techniczne

Dimensions

Masa:	0.56 kg
-------	---------

Features

Bolt:	2xM10
For conductor size:	BLL / BLX 50-157
Ośłona z tworzywa sztucznego:	SP16

Mechanical

Moment dokręcenia:	40 Nm
--------------------	-------

Ratings

ETIM:	EC001062
-------	----------

Specification

Use:	Watertight connector to be used as a temporary earthing connector or as arc protection connector.
------	---

Construction:	The lower section of the body protects the bolts against corrosion and enables the connector easily to be reopened even after years of service. The conductor groove is brushed, greased and toothed to ensure reliable connections.
---------------	--

Construction:

Component	Material
Body	Corrosion resistant aluminium alloy, tensile strength 300 N/mm ²
Bolts	Hot-dip galvanised steel
Horn	Hot-dip galvanised steel

Installation:

It is not necessary to dismantle the connector during the installation work. Unscrew the bolts and place the conductor into the groove. Tighten the bolts with articulated spanner and fork wrench to torque of 40 Nm.

Tools required:

Articulated spanner ST20, fork wrench ST34.

Markings:

SEW 20, Ensto AL 50-157 mm² 40Nm week/year of manufacture

Standard:

EN 50397-2

ETIM

ETIM**Surface protection:**

Bare

Material main conductor:

Aluminium

Material branch conductor:

Aluminium

Clamping channel opening main conductor:

Both sides open

Clamping channel opening branch conductor:

Both sides open

Type of connection:

Insulation piercing connector IPC

Opakowanie

Opakowanie**Unit:**

PCS

Size:

24

Length:

400 mm

Width:

265 mm

Height:

220 mm

Weight (net):

13.44 kg

Weight (brt):

13.64 kg

Volume:

0.0233

Pallet package**Unit:**

PCS

Size:

864

Length:

1200 mm

Width:

800 mm

Height:	1020 mm
Weight (net):	483.84 kg
Weight (brt):	504 kg
Volume:	0.9792