


Amp.	Bieguny	pakowane po / szt.	110V~ 50/60Hz 4h	230V~ 50/60Hz 3p=6h 4p+5p=9h	400V~ 50/60Hz 3p=9h 4p+5p=6h	500V~ 50/60Hz 7h	>50-500V~ 100-300Hz 10h	>50-500V~ 301-500Hz 2h
			Nr kat.	Nr kat.	Nr kat.	Nr kat.	Nr kat.	Nr kat.

Wymiary wys. x szer. x głęb. = 170x118x173; 1xM40; 2xM32


63	3	2	133-4	133-6	133-9	133-7	133-10	133-2
63	4	2	134-4	134-9	134-6	134-7	134-10	134-2
63	5	2	135-4	135-9	135-6	135-7	135-10	135-2



135-6

Wymiary wys. x szer. x głęb. = 262x162x195; 1xM40; 2xØ40

63	3	2	1337-4	1337-6	1337-9	1337-7	1337-10	1337-2
63	4	2	1347-4	1347-9	1347-6	1347-7	1347-10	1347-2
63	5	2	1357-4	1357-9	1357-6	1357-7	1357-10	1357-2




1357-6

Wymiary wys. x szer. x głęb. = 262x162x205; 1xØ50; 2xØ40

125	3	1	143-4	143-6	143-9	143-7	143-10	143-2
-----	---	---	-------	--------------	-------	-------	--------	-------

Wymiary wys. x szer. x głęb. = 262x162x205; 1xM63; 2xØ40

125	4	1	144-4	144-9	144-6	144-7	144-10	144-2
125	5	1	145-4	145-9	145-6	145-7	145-10	145-2



145-6



Akcesoria (dławnice) patrz str. 51

