




Shunt release, 110-415V, 1HP

Part no. ZP-ASA/230
Article no. 248439

Delivery program

Basic function			Accessories for miniature circuit breaker Accessories for combined residual-current/power circuit-breakers
Basic function accessories			Shunt release
Application			Switchgear for industrial and advanced commercial applications
Product range			Accessory
Side mounting			for fitting on left to: FAZ, FRBmM-1N, Z-MS
Contact sequence			

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.	°C	-5	
Operating ambient temperature max.	°C	40	

Technical data ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary contact unit for distribution board (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss8.1-27-14-35-02 [AKE327010])			
Device fitting			-
Additional equipment			Shunt release (for power circuit breaker)
Attached at delivery			No
Assembly width (TE)			1
Number of normally open contacts			0
Number of normally closed contacts			0
Number of change-over contacts			0
Number of fault-signal switches			0
Rated switch current	A	0	
Nominal rated voltage	V	230	
Control voltage type		AC	
With autotest for earth leakage function		No	
Suitable for max. number of poles main contact unit (total)		1	
Suitable for max. current main contact unit	A	2.1	

Dimensions

