




- Features:**
- Section height 2000 mm
 - Degree of protection IP31 or IP55
 - Protection class I
 - Opening angle
 - 180° with separate mounting
 - 170° with side-by-side installation¹⁾
 - Exchangeable door hinges
 - Component mounting area for outgoers:
 - IP31 1800 mm
 - IP55 1900 mm



Busbar <i>I_e</i>	Section depth	Module width	Connection area width	Section width	Type Frames top/bot- tom	Type Vertical profiles	Type Fitting kit for outgoers with circuit-breakers
A	mm	mm	mm	mm	Article no. for 1 kit	Article no. for 1 kit	Article no. for 1 kit
Sections for rear dropper bar position up to form 2b, actuation behind component mounting door (interchangeable connection and dropper bar / component mounting area), max. installation depth = 284 mm							
≤ 3200	600	425	200	600	XSFB0606 284235	XSFH20 284245	XSMFIB0606 284253
		600	200	800	XSFB0806 284238	XSFH20 284245	XSMFIB0606 284253
		425	400	800	XSFB0806 284238	XSFH20 284245	XSMFIB0606 284253
		600	400	1000	XSFB1006 284241	XSFH20 284245	XSMFIB0606 284253
4000	800	425	200	600	XSFB0608 284236	XSFH20 284245	XSMFIB0608 284254
		600	200	800	XSFB0808 284239	XSFH20 284245	XSMFIB0608 284254
		425	400	800	XSFB0808 284239	XSFH20 284245	XSMFIB0608 284254
		600	400	1000	XSFB1008 284242	XSFH20 284245	XSMFIB0608 284254
Sections for rear dropper bar position up to form 4b, actuation external or behind component mounting door (interchangeable connection and dropper bar / component mounting area), max. installation depth = 274 mm (with cover plate max 205 mm)							
≤ 3200	600	425	175	600	XSFB0606 284235	XSFH20 284245	XSMFDB0406 284246
		600	200	800	XSFB0806 284238	XSFH20 284245	XSMFDB0606 284248
		425	375	800	XSFB0806 284238	XSFH20 284245	XSMFDB0406 284246
		600	400	1000	XSFB1006 284241	XSFH20 284245	XSMFDB0606 284248
4000	800	425	175	600	XSFB0608 284236	XSFH20 284245	XSMFDB0408 284247
		600	200	800	XSFB0808 284239	XSFH20 284245	XSMFDB0608 284249
		425	375	800	XSFB0808 284239	XSFH20 284245	XSMFDB0408 284247
		600	400	1000	XSFB1008 284242	XSFH20 284245	XSMFDB0608 284249

Notes ¹⁾ Order alternative hinge for 180° with side-by-side mounting, see page 11/2



Type Component mounting section door in section width ²⁾ – Component mounting section door ³⁾				Type Cable coupling area door ²⁾	Type Back plate	
IP31 Ventilated left	IP31 Ventilated right	IP55 solid	IP55 Transparent, design version	IP55 solid	IP31 Ventilated	IP55
Article no. 1 off each	Article no. 1 off each	Article no. 1 off each	Article no. 1 off each	Article no. 1 off each	Article no. 1 off each	Article no. 1 off each
XSDMLV2006 284210	XSDMRV2006 284219	XSDMC2006 284199	XSDMD2006 284204	–	XSWV2006 284361	XSWC2006 284356
XSDMLV2008 284211	XSDMRV2008 284220	XSDMC2008 284200	XSDMD2008 284701	–	XSWV2008 284362	XSWC2008 284357
XSDMLV2008 284211	XSDMRV2008 284220	XSDMC2008 284200	XSDMD2008 284701	–	XSWV2008 284362	XSWC2008 284357
XSDMLV2010 284212	XSDMRV2010 284221	XSDMC2010 284201	–	–	XSWV2010 284363	XSWC2010 284358
XSDMLV2006 284210	XSDMRV2006 284219	XSDMC2006 284199	XSDMD2006 284204	–	XSWV2006 284361	XSWC2006 284356
XSDMLV2008 284211	XSDMRV2008 284220	XSDMC2008 284200	XSDMD2008 284701	–	XSWV2008 284362	XSWC2008 284357
XSDMLV2008 284211	XSDMRV2008 284220	XSDMC2008 284200	XSDMD2008 284701	–	XSWV2008 284362	XSWC2008 284357
XSDMLV2010 284212	XSDMRV2010 284221	XSDMC2010 284201	–	–	XSWV2010 284363	XSWC2010 284358
XSDFMLV2004 284188	XSDFMRV2004 284190	XSDFMC2004 284184	XSDFMD2004 284186	XSDFCC2002 284182	XSWV2006 284361	XSWC2006 284356
XSDFMLV2006 284189	XSDFMRV2006 284191	XSDFMC2006 284185	XSDFMD2006 284187	XSDFCC2002-1 284700	XSWV2008 284362	XSWC2008 284357
XSDFMLV2004 284188	XSDFMRV2004 284190	XSDFMC2004 284184	XSDFMD2004 284186	XSDFMC2004 284184	XSWV2008 284362	XSWC2008 284357
XSDFMLV2006 284189	XSDFMRV2006 284191	XSDFMC2006 284185	XSDFMD2006 284187	XSDFCC2004 284183	XSWV2010 284363	XSWC2010 284358
XSDFMLV2004 284188	XSDFMRV2004 284190	XSDFMC2004 284184	XSDFMD2004 284186	XSDFCC2002 284182	XSWV2006 284361	XSWC2006 284356
XSDFMLV2006 284189	XSDFMRV2006 284191	XSDFMC2006 284185	XSDFMD2006 284187	XSDFCC2002-1 284700	XSWV2008 284362	XSWC2008 284357
XSDFMLV2004 284188	XSDFMRV2004 284190	XSDFMC2004 284184	XSDFMD2004 284186	XSDFMC2004 284184	XSWV2008 284362	XSWC2008 284357
XSDFMLV2006 284189	XSDFMRV2006 284191	XSDFMC2006 284185	XSDFMD2006 284187	XSDFCC2004 284183	XSWV2010 284363	XSWC2010 284358

Notes ²⁾ Doors always required.
³⁾ Door optional, if installed devices are covered off by front surrounds; always required for IP55.