


Q18D(R)...., Q25D(R), Pushbutton actuators, IP65



Front dimensions
18 x 18 mm

Front dimensions
25 x 25 mm

Button plate	Color	Part no. Article no.	Part no. Article no.	Price See price list	Std. pack	Information relevant for export to North America  	
		Q18D-11 086332	Q25D-11 090471		10 off  	Product Standards	IEC/EN 60947-5; UL 508; CSA-C22.2 No. °14-05; CE marking
		Q18D-10 086299	Q25D-10 090421			UL File No.	E29184
		Q18D-20 054041	Q25D-20 054038			UL CCN	KCR
		Q18D-19 054040	Q25D-19 054039			CSA File No.	46552
		Q18D-SW 086788	Q25D-SW 087230			CSA Class No.	3211-03
		Q18D-WS 086752	Q25D-WS 086808			NA Certification	UL Listed, CSA certified
		Q18D-GN 086450	Q25D-GN 086409			Degree of Protection	UL/CSA Type 1
		Q18D-RT 086713	Q25D-RT 086444				
		Q18D-GE 086417	Q25D-GE 086343				
		Q18D-BL 086384	Q25D-BL 086328				
	—	Q18D-X 093623	Q25D-X 093624				
		Q18DR-SW 086269	Q25DR-SW 088739				
		Q18DR-WS 086243	Q25DR-WS 088701				
		Q18DR-GN 086176	Q25DR-GN 088531				
		Q18DR-RT 086209	Q25DR-RT 088627				
		Q18DR-GE 090482	Q25DR-GE 088404				
		Q18DR-BL 090241	Q25DR-BL 088110				
	—	Q18DR-X 093625	Q25DR-X 093626				



Accessories	Page
Assembly aids and accessories	→15
Contact elements	
N/O	→3
NC	→3

Contact elements (Admissible operating voltage: 5 – 250 V)

→ Safety function by positive opening according to IEC/EN 60947-5-1

Circuit symbol

Contact sequence

Color


Part no.
Article no.

Price
See price list

Std. pack

Information relevant for export to North America
 

N/O = normally open contact
NC = normally closed contact

1 N/O	—				E10 090351	50 off  	Product Standards	IEC/EN 60947-5; 508; CSA-C22.2 No. 14-05; CE ^o marking E29184
—	1 NC 				E01 090401	50 off  	UL File No.	E29184
							UL CCN	NKCR
							CSA File No.	46552
							CSA Class No.	3211-03
							NA Certification	UL Listed, CSA certified

Notes

x = Sequence number on front element
y = Function number on contact element