




Moeller FK4810-1143GB-INT

Moeller FK4810-1143GB-INT



- Features:**
- Rated current up to 630 A
 - I_{cc} (400 V AC) up to 100 kA
 - Fixed mounted (plug-in or withdrawable unit)
 - 3-pole and 4-pole
 - External actuation or behind component area door
 - Vertical installation¹⁾



	I_n up to	Installation type	Poles	Number of devices per module	Module height	Module width	Type Mounting plate	Type Front surround ²⁾
	A	A			mm	mm	Article no. 1 off each	Article no. 1 off each
Circuit-breakers								
Mounting kit for 3-pole circuit-breaker and fuse switch-disconnector (installation of a switch insulating surround not possible.)								
NZM1 ³⁾	125	Fixed	3	2	300	425	XMN131204MV 284000	XMN131204CV 283999
				3	300	600	XMN131206MV 284002	XMN131206CV 284001
NZM2 ³⁾	250	Fixed	3	2	400	425	XMN231604MV 284016	XMN231604CV 284015
				3	400	600	XMN231606MV 284018	XMN231606CV 284017
		Plug-in	3	2	600	425	XMN232404MV 284020	XMN232404CV 284019
				3	600	600	XMN232406MV 284022	XMN232406CV 284021
NZM3 ³⁾	630	Fixed	3	1	600	425	XMN332404MV 284046	XMN332404CV2 284044
				2	600	600	XMN332406MV 284051	XMN332406CV2 284049
		Drawer unit	3	1	600	425	XMN332404MV 284046	XMN332404CV1 284042
					600	600	XMN332406MV 284051	XMN332406CV1 284047
GS(TA) 00 ⁴⁾ / GSTA3 ⁴⁾	160	Fixed	3	3/1	300	600	XMG031206MV 283952	–
GS(TA) 1 ⁴⁾	250	Fixed	3	2	400	600	XMG131606MV 283953	–
GS(TA) 2 ⁴⁾	400	Fixed	3	1	400	600	XMG231606MV 283954	–
Fitting kit for 4-pole circuit-breaker (switch insulating surround required for degree of protection and must be ordered separately. Installation of 3-pole circuit-breaker is possible.)								
NZM1 ³⁾	125	Fixed	4	2	300	425	XMN141204MV 284008	XMN141204CV 284007
				3	300	600	XMN141206MV 284010	XMN141206CV 284009
NZM2 ³⁾	250	Fixed	4	1	400	425	XMN241604MV 284029	XMN241604CV 284028
				2	400	600	XMN241606MV 284031	XMN241606CV 284030
		Plug-in	4	1	600	425	XMN242404MV 284033	XMN242404CV 284032
				2	600	600	XMN242406MV 284035	XMN242406CV 284034
NZM3 ³⁾	630	Fixed	4	1	600	425	XMN342404MV 284062	XMN342404CV2 284060
				1	600	600	XMN342406MV 284067	XMN342406CV2 284065
		Drawer unit	4	1	600	425	XMN342404MV 284062	XMN342404CV1 284058
				1	600	600	XMN342406MV 284067	XMN342406CV1 284063

- Notes**
- ¹⁾ If necessary consider additional space for the connection of larger outgoer cables.
²⁾ Front surround can be attached with or without hinge.
³⁾ Installation of the covers for NZM...-XKSA connections, NZM...-XKR connection on rear and the 4-pole NZM2-4-XFI... fault-current trip not possible.
⁴⁾ Installation possible without front surround only.

- Features:**
- Rated current up to 630 A
 - I_{cc} (400 V AC) up to 100 kA
 - Fixed mounted (plug-in or withdrawable unit)
 - 3-pole and 4-pole
 - External actuation or behind component area door
 - Vertical installation¹⁾

	Installation type	Number of devices per module	Module height	Module width	Type Mounting plate	Type Front surround ²⁾
	A		mm	mm	Article no. 1 off each	Article no. 1 off each
FAZ,... ³⁾ , PKZ... ⁴⁾	Fixed	1 × 12 SU	150	425	XMMC0604M 283980	XMMC0604C 283979
		1 × 24 SU	150	600	XMMC0606M 283982	XMMC0606C 283981
		1 × 12 SU	200	425	XMMC0804M 283984	XMMC0804C 283983
		1 × 24 SU	200	600	XMMC0806M 283986	XMMC0806C 283985
		2 × 12 SU	300	425	XMMC1204M 283988	XMMC1204C 283987
		2 × 24 SU	300	600	XMMC1206M 283990	XMMC1206C 283989
		2 × 12 SU	400	425	XMMC1604M 283992	XMMC1604C 283991
		2 × 24 SU	400	600	XMMC1606M 283994	XMMC1606C 283993
Terminals ³⁾	–	1 × 12 SU	150	425	XMMC0604M 283980	XME0604C 283934
		1 × 24 SU	150	600	XMMC0606M 283982	XME0606C 283936
		2 × 12 SU	300	425	XMMC1204M 283988	XME1204C 283946
		2 × 24 SU	300	600	XMMC1206M 283990	XME1206C 283947

- Notes**
- ¹⁾ If necessary consider additional space for the connection of larger outgoer cables.
²⁾ Front surround can be attached with or without hinge.
³⁾ Mounting plate fitting kit is comprised of an aluminium mounting rail incl. attachment kit; for Form 2b the XME...M mounting plate must be complemented.
⁴⁾ Installation of S...PKZ... contact module and CL-... current limiter not possible.