

Fuse Switch Disconnectors XNH...

Fuse Switch Disconnectors XNH...

- Degree of protection IP2XC in operating mode
- According to IEC/EN 60947-3
- AC 690 V / DC 440 V
- Conditional rated short-circuit current 120kA (500V) and 100kA (690V)
- Reaction to fire according to UL 94, self-extinguishing
- Current paths of electrolytic copper, silver-plated
- For fixing on mounting plates and DIN rails
- Fuse Control Light with optical signalling of triggered fuse-links
- Fuse Control FCE with electronic monitoring of fuse-links

 VT64015	Size	Type of connection	I _e (A)	Type designation	Article No.	Pack (pcs.)

Basic

3-pole for mounting plate

vt61615	00	Flat connection M8 max. 95 mm ²	160	XNH00-A160	183025	1
		Box terminal 1.5 - 95 mm ²	160	XNH00-A160-BT	183026	1
	1	Flat connection M10 max. 150 mm ²	250	XNH1-A250	183043	1
		Box terminal 35 - 150 mm ²	250	XNH1-A250-BT	183044	1
	2	Flat connection M10 max. 240 mm ²	400	XNH2-A400	183057	1
		Box terminal 95 - 300 mm ²	400	XNH2-A400-BT	183058	1
	3	Flat connection M10 max. 300 mm ²	630	XNH3-A630	183071	1
		Box terminal 95 - 300 mm ²	630	XNH3-A630-BT	183072	1

Fuse Control Light

3-pole for mounting plate

wa_vt15515	00	Flat connection M8 max. 95 mm ²	160	XNH00-FCL-A160	183027	1
		Box terminal 1.5 - 95 mm ²	160	XNH00-FCL-A160-BT	183028	1
	1	Flat connection M10 max. 150 mm ²	250	XNH1-FCL-A250	183045	1
		Box terminal 35 - 150 mm ²	250	XNH1-FCL-A250-BT	183046	1
	2	Flat connection M10 max. 240 mm ²	400	XNH2-FCL-A400	183059	1
		Box terminal 95 - 300 mm ²	400	XNH2-FCL-A400-BT	183060	1
	3	Flat connection M10 max. 300 mm ²	630	XNH3-FCL-A630	183073	1
		Box terminal 95 - 300 mm ²	630	XNH3-FCL-A630-BT	183074	1

Fuse Control FCE

3-pole for mounting plate

vt02416	00	Flat connection M8 max. 95 mm ²	160	XNH00-FCE-A160	183029	1
		Box terminal 1.5 - 95 mm ²	160	XNH00-FCE-A160-BT	183030	1
	1	Flat connection M10 max. 150 mm ²	250	XNH1-FCE-A250	183047	1
		Box terminal 35 - 150 mm ²	250	XNH1-FCE-A250-BT	183048	1
	2	Flat connection M10 max. 240 mm ²	400	XNH2-FCE-A400	183061	1
		Box terminal 95 - 300 mm ²	400	XNH2-FCE-A400-BT	183062	1
	3	Flat connection M10 max. 300 mm ²	630	XNH3-FCE-A630	183075	1
		Box terminal 95 - 300 mm ²	630	XNH3-FCE-A630-BT	183076	1

1-pole for mounting plate

	00	Flat connection M8 max. 95 mm ²	160	XNH00-1-A160	183031	1
		Box terminal 1.5 - 95 mm ²	160	XNH00-1-A160-BT	183032	1
	1	Flat connection M10 max. 150 mm ²	250	XNH1-1-A250	183049	1
		Box terminal 35 - 150 mm ²	250	XNH1-1-A250-BT	183050	1
	3	Flat connection M10 max. 300 mm ²	400/630	XNH32-1-A630	183063	1
		Box terminal 95 - 300 mm ²	400/630	XNH32-1-A630-BT	183064	1