



HE 35 W/830



Opis produktu: HE 35 W/830
EAN / Produkt: 4050300464763
Ilość: Nieopakowane (UNV) zawiera 1 Sztuka (ST)

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=EN&~country=PL&it_p=4050300464763

Zastosowania	
Suitable for indoor	Yes

Opis ogólny	
SEG nr	8328565
Ssti-Number	4931083
Trzonek (standardowe rozwiązanie)	G5
Energy Label - EEI	A
Recykling	yes

Techniczny - Dane elektryczne	
Moc znamionowa [W] (opakowanie)	35 W
Moc konstrukcji [W]	35.5 W
Rated lamp efficacy (standard condition)	94 lm/W
Rated lampeffic. (HF data)	Under clarification by authority and standardization body

Techniczny - Dane geometryczne	
Średnica rury [mm]	16 mm
Długość [mm]	1449 mm
Długość oprawki do trzonka pinowego / po	1449 mm

Techniczny - Trwałość	
Nominal lamp life time	16000 h
Trwałość użytkowa	16000 h ¹⁾
Trwałość [h]	20000 h ²⁾

Techniczny - Dane świetlne	
Nominal luminous flux	3320 lm
Rated luminous flux	3320 lm
Strumień świetlny [lm]	3300 lm ³⁾
Strumień świetlny znam. temp. 35°C	3650 lm
Barwa światła	830
Rated colour temperature	3000 K
Wskaźnik oddawania barw Ra	min. 80 maks. 89
Barwa światła zgodna z EN 12464-1	LUMILUX Warm White
Lamp mercury content	1.9 mg
Rated LLMF at 2000h	0.95
Rated LLMF at 4000h	0.92
Rated LLMF at 6000h	0.91
Rated LLMF at 8000h	0.90
Rated LLMF at 12000h	0.90
Rated LLMF at 16000h	0.89
Rated LLMF at 20000h	0.89



HE 35 W/830

Techniczny - Dane świetlne

Rated lamp surviv.factor 2000h	0.99
Rated lamp surviv.factor 4000h	0.99
Rated lamp surviv.factor 6000h	0.99
Rated lamp surviv. factor 8000h	0.99
Rated lamp surviv.factor 12000h	0.99
Rated lamp surviv.factor 20000h	0.50
Operation mode LLMF/LSF	HF

Techniczny - Temperatury

Rated ambient temp.w.max.lum	35.0 °C
------------------------------	---------

Rodzaj opakowania

EAN	Rodzaj opakowania i zawartość	Wymiary: w x sz x dł	Waga brutto	Objętość:
4050300464763	Nieopakowane zawiera 1 Sztuka	17,000 mm x 17,000 mm x 1.462,000 mm	138,000 g (0,000 g)	0,423 dm3
4050300464770	Karton wysyłkowy zawiera 40 Sztuka	194,000 mm x 93,000 mm x 1.500,000 mm	6.258,000 g (0,000 g)	27,063 dm3

1) with preheat ECG

2) With preheat ECG

3) These values are reached at 25 °C (acc. to IEC 60081 lumen values for fluorescent lamps must always be specified for 25 °C).
These lamps offer even more luminous flux if they are operated wi