



HO 39 W/840



Opis produktu: HO 39 W/840
EAN / Produkt: 4050300453538
Ilość: Nieopakowane (UNV) zawiera 1 Sztuka (ST)

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=EN&~country=PL&it_p=4050300453538

Zastosowania	
Suitable for indoor	Yes

Opis ogólny	
SEG nr	8328629
Ssti-Number	4931284
Trzonek (standardowe rozwiązanie)	G5
Energy Label - EEI	A
Recykling	yes

Techniczny - Dane elektryczne	
Moc znamionowa [W] (opakowanie)	39 W
Moc konstrukcji [W]	38 W
Rated lamp efficacy (standard condition)	82 lm/W
Rated lampeffic. (HF data)	Under clarification by authority and standardization body

Techniczny - Dane geometryczne	
Średnica rury [mm]	16 mm
Długość [mm]	849 mm
Długość oprawki do trzonka pinowego / po	849 mm

Techniczny - Trwałość	
Nominal lamp life time	16000 h
Trwałość użytkowa	18000 h ¹⁾
Trwałość [h]	24000 h ²⁾

Techniczny - Dane świetlne	
Nominal luminous flux	3100 lm
Rated luminous flux	3100 lm
Strumień świetlny [lm]	3100 lm ³⁾
Strumień świetlny znam. temp. 35°C	3500 lm
Barwa światła	840
Rated colour temperature	4000 K
Wskaźnik oddawania barw Ra	min. 80 maks. 89
Barwa światła zgodna z EN 12464-1	LUMILUX Cool White
Lamp mercury content	1.9 mg
Rated LLMF at 2000h	0.95
Rated LLMF at 4000h	0.92
Rated LLMF at 6000h	0.91
Rated LLMF at 8000h	0.90
Rated LLMF at 12000h	0.90
Rated LLMF at 16000h	0.89
Rated LLMF at 20000h	0.89



HO 39 W/840

Techniczny - Dane świetlne	
Rated lamp surviv.factor 2000h	0.99
Rated lamp surviv.factor 4000h	0.99
Rated lamp surviv.factor 6000h	0.99
Rated lamp surviv. factor 8000h	0.99
Rated lamp surviv.factor 12000h	0.99
Rated lamp surviv.factor 20000h	0.50
Operation mode LLMF/LSF	HF

Techniczny - Temperatury	
Rated ambient temp.w.max.lum	35.0 °C

Rodzaj opakowania				
EAN	Rodzaj opakowania i zawartość	Wymiary: w x sz x dł	Waga brutto	Objętość:
4050300453538	Nieopakowane zawiera 1 Sztuka	17,000 mm x 15,000 mm x 863,000 mm	79,000 g (0,000 g)	0,155 dm3
4050300453545	Karton wysylkowy zawiera 40 Sztuka	194,000 mm x 92,000 mm x 900,000 mm	3.614,000 g (0,000 g)	15,365 dm3

1) with preheat ECG

2) With preheat ECG

3) These values are reached at 25 °C (acc. to IEC 60081 lumen values for fluorescent lamps must always be specified for 25 °C).
These lamps offer even more luminous flux if they are operated wi