



TL-D Standard Colours

TL-D 18W/54-765 1SL/25

TL-D Standard Colors lamps (tube diameter of 26 mm) create atmospheres from warm white to cool daylight. Lamps with moderate efficacy and color rendering.

Product data

General Information				
Cap-Base	G13 [Medium Bi-Pin Fluorescent]			
Life To 10% Failures (Nom)	10000 h			
Life To 50% Failures (Nom)	13000 h			
Light Technical				
Color Code	54-765			
Luminous Flux (Nom)	1050 lm			
Color Designation	Cool Daylight			
Lumen Maintenance 10000 h (Nom)	75 %			
Lumen Maintenance 2000 h (Nom)	90 %			
Lumen Maintenance 5000 h (Nom)	80 %			
Chromaticity Coordinate X (Nom)	315			
Chromaticity Coordinate Y (Nom)	341			
Correlated Color Temperature (Nom)	6200 K			
Color Rendering Index (Nom)	72			
Operating and Electrical				
Power (Rated) (Nom)	18.0 W			
Lamp Current (Nom)	0.360 A			
Voltage (Nom)	59 V			

Controls and Dimming			
Dimmable	Yes		
Approval and Application			
Energy Efficiency Label (EEL)	В		
Mercury (Hg) Content (Nom)	8.0 mg		
Energy Consumption kWh/1000 h	22 kWh		
Product Data			
Full product code	692341077020900		
Order product name	TL-D 18W/54-765 1SL/25		
EAN/UPC - Product	6923410770209		
Order code	928048005453		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	25		
Material Nr. (12NC)	928048005453		
Net Weight (Piece)	0.070 kg		
ILCOS Code	FD-18/62/2A-E-G13		

Datasheet, 2016, December 27 data subject to change

TL-D Standard Colours

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing

Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL-D 18W/54-765 1SL/25	28 mm	589.8 mm	596.9 mm	594.5 mm	604 mm

TL-D 18W/54-765

Photometric data

Lightcolor /54-765

Lightcolor /54-765

