

Product Specification Sheet



Technical Information

Instant Start:	0-100% in lt1s	LED Chip Type:	SMD
EQ-WATTS:	200	IP Rating:	IP65
Watts:	36	Dimmable:	No
Lumens:	2880	Warranty (Years):	2
Beam Angle:	120	PF:	>0.9
Unit Color:	White	CRI:	>70
Body Type:	ABS+PC	Operation Temperature:	-20 to +45°c
Energy Rating:	A+	Input Power:	AC:220-240V,50Hz
Long life:	20,000 Hours	Sensor Compatibility:	Yes

Features

- Waterproof fittings inclusive of T8 LED Tubes
- Transparent PC diffuser with higher light transmittance
- Opaque ABS housing with good mechanical performance
- PG11 waterproof cable gland available for wiring input on one side of the housing
- Silicon gel gasket and PC clips ensuring IP65 protection
- Available in 120 cm and 150 cm
- Long Lifespan, Low maintenance and energy saving
 - Applications Parking Lots, Warehouses, Garages, Storage Docks, Workshops and many more

Packaging

Unit Details		Listing Details	
Gross Weight(GW) Kgs	0.985	EAN Code	3800157616485
Length(Box)mm	1290	Commodity Code	9405403990
Width(Box)mm	70		
Height(Box)mm	70		
Unit CBM	0.007909		
Master Box Packaging			
Master Box Qty (Pcs Per Carton)	12		
Qty Per Pallet	144		

