

Product Specification Sheet



Technical Information

Instant Start:	0-100% in lt1s	IP Rating:	IP65
EQ-WATTS:	50	Dimmable:	No
Watts:	10	Warranty (Years):	2
Lumens:	850	PF:	>0.9
Beam Angle:	110	CRI:	>70
Unit Color:	Black	Operation Temperature:	-25 to +50°c
Body Type:	Aluminium	Input Power:	AC:220-240V,50Hz
Long life:	20,000 Hours	Sensor Compatibility:	Yes
LED Chip Type:	SMD2835		



Features

- Perfect replacement of Metal Hallide Floodlight, High Pressure Sodium Floodlight & Halogen Floodlight
- Available in different color options of White , Day White, Warm White and RGB
 - Fascia glass sealed with SILICONE RUBBER ensuring superior waterproof /airtight performance
 - Premium Quality Aluminium Alloy body
 - High Power LED chip
 - **Corrosion Resistant**
 - Built in driver no external power supply required
 - Excellent coverage for area and façade lighting
 - Available from 10W up to 1000W
 - Application Building Façade, Sports Facilities, Industrial, Commercial Bill Boards & Hoardings, Parking Lots etc



Suitable & Recommended for maximum daily use of 10-12 hours, usage beyond this would void the warranty

Packaging

Unit Details		Listing Details	
Gross Weight(GW) Kgs	0.305	EAN Code	3800157625340
Length(Box)mm	115	Commodity Code	9405403990
Width(Box)mm	120		
Height(Box)mm	30		
Unit CBM	0.000506		
Master Box Packaging			
Master Box Qty (Pcs Per Carton)	40		
Qty Per Pallet	2400		

