

Product Specification Sheet



VT-8027 PIR CEILING SENSOR(FLAT)

Beam Angle 360

Dimensions 625x220x265mm

SKU:5086





Technical Information

Beam Angle:	360
Ambient Light:	
Detection Distance:	Max. 6m(
Detection Motion Speed:	0.6-1.5m/s
Rated Load:	Max. 2000W
Time Delay:	Min. 10sec±3sec, Max. 15min±2min
Detection Range:	360°
Unit Color:	White

 Body Type:
 PC

 Sensor Type:
 Infrared

 Long life:
 20,000 Hours

 IP Rating:
 IP20

 Dimmable:
 No

 Warranty (Years):
 2

 Operation Temperature:
 -25 to +50°c

 Input Power:
 AC:220-240V,50Hz

Features

- Downlight series built with High quality COB LED chip
- Premium Quality Power Driver with high quality power factor correction
- Die cast aluminium housing with heat sink for optimum thermal mangement
- Multi faceted aluminium reflector for optimum light intensity
- Lumen efficiency range starting from 65lm/W up to 120LM/W
- ✓ Non-Flickering No UV Radiation
- Low Maintenance and Easy Installation
- Available from 3W to 40W
 - Applications Residential, Showrooms, Hotels & Boutiques etc

Noto:



Suitable & Recommended for maximum daily use of 10-12 hours, usage beyond this would void the warranty

Packaging

Unit Details

 Gross Weight(GW) Kgs
 0.14

 Unit CBM
 0.000525

Master Box Packaging

 Master Box Qty (Pcs Per Carton)
 50

 Qty Per Pallet
 1500

Listing Details

EAN Code 3800157609173

