

# **Product Specification Sheet**



#### VT-8029 PIR CEILING SENSOR

Beam Angle 360

Dimensions 10X78X82mm

SKU:5090





### **Technical Information**

| Beam Angle:             | 360                              |
|-------------------------|----------------------------------|
| Ambient Light:          |                                  |
| Detection Distance:     | Max. 6m(                         |
| Detection Motion Speed: | 0.6-1.5m/s                       |
| Rated Load:             | Max. 1200W                       |
| Time Delay:             | Min. 10sec±3sec, Max. 15min±2min |
| Detection Range:        | 360°                             |
| Unit Color:             | White                            |

| Body Type:             | PC               |
|------------------------|------------------|
| Sensor Type:           | Infrared         |
| Long life:             | 20,000 Hours     |
| IP Rating:             | IP20             |
| Dimmable:              | No               |
| Warranty (Years):      | 2                |
| Operation Temperature: | -25 to +50°c     |
| Input Power:           | AC:220-240V,50Hz |



#### **Features**

- ✓ Downlight series built with High quality COB LED chip
- Premium Quality Power Driver with high quality power factor correction
- Die cast aluminium housing with heat sink for optimum thermal mangement
- Multi faceted aluminium reflector for optimum light intensity
- Lumen efficiency range starting from 65lm/W up to 120LM/W
- ✓ Non-Flickering No UV Radiation
- Low Maintenance and Easy Installation
- Available from 3W to 40W
  - Applications Residential, Showrooms, Hotels & Boutiques etc





Suitable & Recommended for maximum daily use of 10-12 hours, usage beyond this would void the warranty

## Packaging

**Unit Details** 

 Gross Weight(GW) Kgs
 0.13

 Unit CBM
 0.00068

Master Box Packaging

 Master Box Qty (Pcs Per Carton)
 50

 Qty Per Pallet
 1400

#### **Listing Details**

EAN Code 3800157609210



