



F-2A

Indeks: WACEGF2AOKR

Cęgi elastyczne

Opis

Cęgi	C-4A	C-5A	C-6A	C-7A	F-1A	F-2A	F-3A	F-4A
Prąd znamionowy	1000 A AC	1000 A AC 1400 A DC	10 A AC	100 A AC	3000 A AC			
Maks. prąd prze	1200 A AC	1000 A AC 3000 A DC	20 A AC	100 A AC	10k A AC			
do pomiaru	100 mA	500 mA	10 mA	20 mA	1 A			
	30 Hz...10 kHz	Dc...5 kHz	40 Hz...10 kHz	40 Hz...1 kHz	40 Hz...10 kHz			
Poziom sygnału w	1 mV / 1 A	1 mV / 1 A	100 mV / 1 A	5 mV / 1 A	38,8 μV / 1 A			

Maks. średnica	52 mm	39 mm	20 mm	24 mm	360 mm	235 mm	120 mm	630 mm
przewodu								
Długość otwartych cęgów	—	—	—	—	120 cm	80 cm	45 cm	200 cm
	≤ 0,5%	≤ 1,5%	≤ 1%	0,5%	1%			
Zasilanie bateryjne	—	+	—	—	—			
Długość przewodu	2,2 m	2,2 m	2,2 m	3 m	2,2 m			
Kategoria	IV 300 V	IV 300 V	IV 300 V	III 300 V	IV 600 V			