

ENSTO

SO255S

Tension clamp

Typ SO255S
GTIN 6438100324667
Nazwa Tension clamp
PAS/BLL- 50-70 mm², AlMgSi, shear head
Opis Tension clamp for covered conductors (PAS/BLL AlMgSi and for insulated messengers of aerial MV cables like AHXAMK-WM3 (Multi-wiski). The insulation piercing contact part has silicone seal which prevents the moisture getting into the conductor. Shear head ensures the correct tightening torque.

**Specyfikacje techniczne****Wymiary**

Masa: 1.13 kg

Features

For conductor size: PAS / BLL 50-70 AlMgSi

Mechanical

SMFL: 20 kN

Moment dokręcenia: 40 Nm

SMDL: 18 kN

Certyfikaty

Standardy: EN 50397-2

Specyfikacja

Construction:

Construction:

Component	Material
Body	Corrosion resistant aluminium alloy
Plastic parts	Frost, heat and UV-radiation resistant plastic
Bolts	Hot-dip galvanised steel
Nut with shear-head	Aluminum alloy
Bail	Stainless steel

Installation:

The clamp is opened and the conductor wire is inserted between the wedges. The locking connector is tightened until shear-heads break. The clamp is closed and strained.

Tools required:

17 mm socket wrench

Markings:

ENSTO SO255S, 50-70mm², 40 Nm, week/year of manufacture

Opakowanie

Opakowanie

Unit:	PCS
Size:	9
Length:	505 mm
Width:	260 mm
Height:	215 mm
Weight (net):	10.197 kg

Pallet package

Unit:	PCS
Size:	216
Length:	1200 mm
Width:	800 mm
Height:	1030 mm
Weight (brt):	264.728 kg

