

ENSTO

NAC51S.B

Coupler

Typ	NAC51S.B
GTIN	6418677114182
Nazwa	Coupler EnstoNet
	Black (1, 2, PE, N, 3)
Opis	For flexible, stranded and solid wires. Wire cross-section 0,75-4,0 mm ² . Strain-relief for cables with outer diameter of 6,5-14,5 mm.
Producent	Ensto Finland Oy



Specyfikacje techniczne

Specyfikacje techniczne

UL Wire range: 12 ... 18 AWG

Wymiary

Masa: 25.1 g
Przekrój żyły: 0,75 - 4 mm²
Wymiary l x w x h: 61x59x20

Temperatura

Max. operating temperature: +70 °C
Min. installation temperature: +5 °C
Min. operating temperature: -30 °C (without mechanical stress)

Materiał

Materiał: Poliamid 66

Kolor

Kolor: Czarny

Features

Oznakowanie słupa: 1,2,PE,N,3

Drawing markings

L: 250 mm

Ratings

Napięcie znamionowe:	250 ... 400 V
Stopień ochrony:	IP20
Klasa palności:	UL 94 V-2
Prąd znamionowy:	20 A
ETIM 7:	EC002560 Plug-in connector for plug-in building installation

US specific

UL Rated current:	16 A
--------------------------	------

ETIM

ETIM

Cable diameter:	6.5 ... 14.5 mm
Rated voltage:	400 V
Length:	61 mm
With strain relief:	true
Mechanical coding:	true
Pole codification:	3, N, PE, 2, 1
Colour coding/contact insert:	Black
Material housing:	Polyamide (PA)
Rated current:	20 A
Width:	59 mm
Locking mechanism:	Integrated in plug-in connector
Connection type:	Screw connection
Halogen free:	true
Contact material:	CuZn
Number of poles:	5
Number of connections per pole:	1
Max. continuous temperature resistance strain relief:	70 °C
Pollution degree:	2
Surface finish contacts:	Silver-plated
Degree of protection (IP):	IP20
Height:	20 mm
Max. continuous temperature resistance contact part:	70 °C
Connection cross section (solid-core):	0.75 ... 4 mm ²
Connection cross section (fine-strand):	0.75 ... 4 mm ²
Model:	Plug
Rated surge voltage:	4 kV

Opakowanie

Opakowanie

Unit:	PCS
--------------	-----

Size:	100
Length:	385 mm
Width:	260 mm
Height:	130 mm
Weight (brt):	2.76 kg
Volume:	13.013

Pallet package

Unit:	PCS
Size:	6300
Length:	1200 mm
Width:	800 mm
Height:	1060 mm

