



Potentiometer 10k

Part no.

M22-R10K

Article no.

229491




Front ring gold-plated, # 274150

3 individual screw terminals, $P_{\max} = 0.5 \text{ W}$

Accuracy of resistance value: $\pm 10\%$ (linear)

M22...RH with large operating head

Delivery programme

Contact sequence			
Impedance	R	k#	10
Front ring			Front ring: titanium
For use with			
For use with			DILET... ETR4-70
Rated power	P	W	0.5

General

Standards			IEC/EN 60947 VDE 0660
Lifespan, mechanical			
AC operated	Operations	$\times 10^6$	30
DC operated	Operations	$\times 10^6$	30
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Ambient temperature		°C	
Open		°C	– 25 ... 70
Mounting position			As required
Mechanical shock resistance (IEC/EN 60068-2-27)			
Half-sinusoidal shock, 20 ms		g	
Make contact		g	4
Degree of protection			
Terminals			IP 20

Contacts

Rated impulse withstand voltage	U_{imp}	V AC	6000
Rated insulation voltage	U_i	V AC	600
Rated operational voltage	U_e	V AC	440
Conv. thermal current	I_{th}	A	6
Short-circuit rating without welding			
Fuse		A gG/gL	6

Magnet systems

Duty factor		% DF	100
-------------	--	------	-----

Dimensions

