

Digital tape measure

with new laser technology. Allows a professional user to quickly attain precise measurement results. Simple, intuitive operation. Max. distance in inside spaces: up to approx. 70 m. Max. distance outside: up to 10 m. Measures the shortest distance to the target with dynamic (continuous) measurement. Backlit LCD display. Range, surface and volume measurement. Indirect measurement using Pythagoras. Option of three reference points. Extended memory function. Shock-resistant plastic. 1/4"-thread to attach it to a tripod. Accuracy: 1.5 mm per 70 m. Laser class: II. Battery: 9 V block (included in scope of delivery). Compliant with CE and RoHS

105 x 32 x 60 mm	1	21 1560
------------------	---	---------

Folding ruler

10 sections, length 2 m, mm divisions on both sides; Class III

made of fibre glass, highly elastic, non-conductive	10	21 0008
made of wood, with steel spring	10	21 0004

Pocket tape measure (metal tape measure)

made of 19 mm wide spring band steel, enamelled yellow, in metric scale, easy running automatic measure return with strong stop key, unbreakable ABS housing in modern 2-component design with ergonomic soft rubber inset, with carrying clip

red	5 m	6	21 0065
-----	-----	---	---------

Fibre glass tape measure

13 mm wide, yellow, kink-proof unbreakable fibre glass tape measure, metric scale on one side (metre and centimetre), EC type approval, accuracy class II, with plastic end hook, in closed round capsule of impact-resistant plastic, with crank

	20 m	1	21 0104
	30 m	1	21 0106

Cable or wire gauge

according to Swiss standard (Dätwyler)

in nylon	95 x 35 x 3 mm	1	14 0120
----------	----------------	---	---------

Electronic digital pocket slide caliper

for measuring length, depth, external and internal diameter, rust-free, hardened finish, large LCD display, adjustable zero setting, conversion mm – inch, automatic display switch-off, with thumb roll for fine adjustment and fixing screw, includes batteries and instructions, in black plastic case

	Reading			
	mm	inch		
150 mm / 6"	1/100	1/2000"	1	21 0300

Precision pocket slide caliper

made of stainless steel, completely hardened, with measuring probes, depth measurement and thread table, jaw length 47 mm, with torque fixing, in plastic pouch.

	Measurement		Reading			
	mm	mm	Inch			
matte chrome plated	150	1/20	1/128"	10	21 0202	

Marking gauge

made of steel, flat design, mm division.

	Measurement	Reading		
	range mm	mm		
	0-200	1/10	1	21 2000
	0-250	1/10	1	21 2002

Bow compass

with square legs and box joint, tips hardened.

Radius max. 235 mm	200 mm	1	21 2062
--------------------	--------	---	---------

