

Engineering pliers

without VDE-tested 1000 Volt protective insulation,
with precision box joint for clearance-free, particularly durable guidance, jaw length 75 mm,
gripping surfaces with fine angled cut



straight, flat-round jaws	190 (7.5")	6	10 0082
flat-round jaws, 45° angled	190 (7.5")	6	10 0086



straight, flat-wide jaws	190 (7.5")	6	10 0090
flat-wide jaws, 45° angled	190 (7.5")	6	10 0094

Water pump pliers



according to DIN ISO 8976, with box joint,
self-clamping on the tool, with ridged opening (burner hole), manufactured from chrome-vanadium steel

without handle sleeves	250 (10")	10	10 1222
with handle sleeves	250 (10")	6	10 1224

1000 V plier set, 4 piece



Heavy duty diagonal pliers	200 (8")		10 0528
Telephone pliers with straight jaws	200 (8")		10 0216
Combination pliers	180 (7")		10 0336
Wire stripper	160 (6")		10 0686
		1	10 4020

Plier set, 3 piece

Water pump pliers	250 (10")		10 1224
Telephone pliers with bent jaws	200 (8")		10 0238
Diagonal pliers	160 (6")		10 0574
		1	10 4022



1000 V Diagonal pliers DIAMANT

according to DIN ISO 5749

Cutting performance: A special blade shape, optimises hand power transmission and most suitable material quality ensure astoundingly low cutting forces on all types of cables and wires.

Surface coating: Thanks to new technological possibilities, the diagonal pliers obtain a double primer coat as well as a more refined surface coating that ensure a high level of wear resistance and improved corrosion protection.

Handle sleeves: Ergonomic design handle sleeves in modern 2-component design manufactured from premium with excellent tactile properties, VDE-certified insulation protection up to 1000 Volt AC according to DIN EN 60900:2004.

160	6	10 0000
-----	---	---------

Screw pliers

The patented 2-component screw pliers that have been awarded the Design Prize is the ideal problem solver for embedded, dirty or corrosion-damaged screws.

The special head shape of the pliers securely surrounds the screw head, thus loosening the screws which can no longer be removed with conventional tools.

Single joint with arched, vertically ridged gripping surfaces, for all self-tapping or metric screws from M1 – M3

130	1	10 0350
-----	---	---------

Single joint with induction hardened precision blade (approx. 58 HRC), for hard, medium-hard and soft wire.
Arched, horizontally and vertically ridged gripping surfaces, for all self-tapping or metric screws from M2 – M6

160	1	10 0352
-----	---	---------

