with a pivoting angle of up to 20°,  $\frac{1}{4}$ " x 90 mm,

for assembly applications in deep corners or other tight places. With torque-stable stainless steel casing, hardened, blasted and bronzed. Sliding casing that releases the pivoting function is plated in matt chrome and has a colour ring. Hex ball-end joint of chrome vanadium steel, stainless steel casing ø  $12.0 \times 32$  mm.



# T-handle magnetic bit holder

in modern two-component design, for  $^{1}/_{4}$ " bits of all lengths

85 x 95 12 11 4500	in two component design, for	74 Dita of all lengths			
		85 x 95	12	11 4500	



## Bit case, 10 piece

case cap with star-shaped holder for bits and universal holders for slot-head screws

4 - 5.5 - 7 mm width
for Phillips cross-head screws
PH 1 - PH 2 - PH 3
for Pozidriv cross-head screws











## Handy bit cases

each with a 60 mm magnetic holder. The box can also be used directly as an assembly tool. with 6 bits

for slot-head screws 5.5 $\times$ 0.8 - 6.5 $\times$ 1.2	
for Phillips cross-head screws PH 1 + PH 2	







for Phillips cross-head screws PH 1, PH 2 (2 pieces), PH 3

17 piece	1	11 4596	
with 2 TORX $^{\circ}$ bits each of size T 10 - T 20 - T 25			
7 piece	1	11 4597	







#### **COMFORT** bit sets

in an impact-resistant plastic box with a practical opening mechanism to provide quick access to individual bits and magnetic bit holders.

Magnetic holder 60 mm for <sup>1</sup> / <sub>4</sub> " bit drive
for Phillips cross-head screws PH 1, PH 2
for Pozidriv cross-head screws PZ 1, PZ 2
for TORX $^{\circ}$ size T 15, T 20, T 25, T 30

Slot-head screws 0.8 mm, 1.0 mm		
11 piece	1	11 4590
Magnetic holder 90 mm for <sup>1</sup> / <sub>4</sub> " bit drive		

Magnetic holder with quick-fit coupling 60 mm for $^{1}/_{4}$ " bit drive
for TORX $^{\circ}$ size T 10, 2x T 15, 2x T 20, T 25, T 30
for TORX $^{\circ}$ with bore size T 10, 2x T 15, 2x T 20, T 25, T 30
for cross-head screws Phillips PH 1, 3x PH 2, PH 3
for cross-head screws Pozidriv PZ 1, 3x PZ 2, PZ 3
Hex socket 4.0 mm, 5.0 mm, 6.0 mm

Slot-head screws 0.8 mm, 1.0 mm, 1.2 mm		
32 piece	1	11 4592





3010	



Blade size (W x H x L mm)

Advice and ordering: Phone: +49 (0) 02191/3718-01, Fax: +49 (0) 2191/3718-85, E-Mail: order@cimco.de

